

1424317

https://www.phoenixcontact.com/pc/products/1424317

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, Universal, 5-position, Socket, straight, M12, coding: A, on free cable end, Rear mounting, M16 x 1.5, Individual wires, cable length: 0.75 m,  $0.34 \text{ mm}^2$ , TPE litz wire, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1239478

### Your advantages

- · Preassembled with litz wires for immediate use
- · Customer-specific assemblies and litz wire lengths available
- Sealed on the litz wire side for optimum leak-tightness
- All standard pin assignments and codings for signal, data, and power transmission with a uniform design-in design
- · For high transmission safety: shield connection to the housing with optional EMC nut
- · SPEEDCON fast locking system reduces cabling times

#### Commercial data

Item number	1424317
Packing unit	1 pc
Minimum order quantity	100 pc
Product key	ABQCHB
GTIN	4046356729130
Weight per piece (including packing)	41 g
Weight per piece (excluding packing)	30.3 g
Customs tariff number	85444290
Country of origin	DE



1424317

https://www.phoenixcontact.com/pc/products/1424317

#### Technical data

#### **Notes**

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.	
Order information:	Lock nut is included in the scope of delivery	
General	Contact connection method: Crimp connection	

#### Safety note

Safety n	ote
----------	-----

WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- WARNING: Commission properly functioning products only.
   The products must be regularly inspected for damage.
   Decommission defective products immediately. Replace damaged products. Repairs are not possible.
- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
- The products are suitable for applications in plant, controller, and electrical device engineering.
- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductive connector housings must be grounded
- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
- Observe the corresponding technical data. You will find information:
- o On the product
- o On the packing label
- o In the supplied documentation
- o Online at phoenixcontact.com/products under the product
- · Only use tools recommended by Phoenix Contact
- Use a protective cap to protect connectors that are not in use.



1424317

https://www.phoenixcontact.com/pc/products/1424317

	The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
	<ul> <li>Ensure that the protective or functional ground has been properly connected.</li> </ul>
	<ul> <li>VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector</li> </ul>
	<ul> <li>The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).</li> </ul>
Mounting	
Mounting type	Rear mounting M16 x 1.5 With flat nut
Assembly note	With flat nut
Product properties	
• •	
Product type	Circular connectors (device side)
Sensor type	Universal
Number of positions  No. of cable outlets	5
Shielded	1
	no
Coding	A M12
Thread type	WIIZ
Data management status	
Article revision	12
Insulation characteristics	
Overvoltage category	II
Degree of pollution	3
Material specifications	
Flammability rating according to UL 94	V0
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated
Conductor material	Tin-plated Cu litz wires
Electrical properties	
Rated surge voltage	1.5 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U <sub>N</sub>	60 V
Nominal current I <sub>N</sub>	4 A
IV	



1424317

https://www.phoenixcontact.com/pc/products/1424317

Max. conductor resistance 57.6 m $\Omega/m$	
Connection data	
Conductor connection	
Connection method	Individual wires
Contact connection type	Socket
Conductor cross section	0.34 mm²
Tightening torque	3 Nm 4 Nm (Installation-side)
Mechanical properties	
Mechanical data	
Insertion/withdrawal cycles	> 100
Connection 1	
Head design	Socket
Head cable outlet	straight
Head thread type	M12
Coding	A
Connection 2	
Head design	free cable end
Cable/line	
Cable length	0.75 m
Cable type	TPE litz wire
Signal type/category	Universal
Wire diameter incl. insulation	1.2 mm ±0.07 mm
Single wire, color	black, brown,blue, white, gray
Cable cross section	0.34 mm²
Conductor material	Tin-plated Cu litz wires
Conductor structure signal line	7x 0.25 mm
AWG signal line	22
Material wire insulation	TPE
Thickness, insulation	0.21 mm
Nominal voltage, cable	300 V
Test voltage, cable	2000 V AC
Cable resistance	≤ 57.6 mΩ/m
Cable insulation resistance	≥ 20 MΩ*km
Ambient temperature (operation)	-40 °C 85 °C (cable, fixed installation)
	-25 °C 85 °C (Cable, flexible installation)



1424317

https://www.phoenixcontact.com/pc/products/1424317

#### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP67 (When plugged in)
	IP65 (When plugged in)
	IP65/IP67
Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)
	-25 °C 85 °C (cable, fixed installation)
	-25 °C 85 °C (Cable, flexible installation)
	-40 °C 85 °C (cable, fixed installation)

### Standards and regulations

#### M12

Standard designation	M12 connector	
Standards/specifications	IEC 61076-2-101	





1424317

https://www.phoenixcontact.com/pc/products/1424317

## Drawings

### Circuit diagram






Pin assignment M12 socket, 5-pos., A-coded, socket side view



1424317

https://www.phoenixcontact.com/pc/products/1424317



I = current strength, T = ambient temperature



1424317

https://www.phoenixcontact.com/pc/products/1424317

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/1424317

.71	cUL Recognized Approval ID: E118976-20100522			
	Nominal voltage $\mathbf{U}_{N}$	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
	60 V	4 A	22 - 22	-

<i>9</i> 7	UL Recognized Approval ID: E118976-20100522				
		Nominal voltage U <sub>N</sub>	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
		60 V	4 A	22 - 22	-

c <b>711</b> us	cULus Recognized Approval ID: E221474-20140616				
		Nominal voltage U <sub>N</sub>	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
		60 V	4 A	22 - 20	-

cULus Recognized



1424317

https://www.phoenixcontact.com/pc/products/1424317

### Classifications

#### **ECLASS**

UNSPSC 21.0

	ECLASS-11.0	27440102		
	ECLASS-12.0	27440116		
	ECLASS-13.0	27440116		
ETIM				
	ETIM 9.0	EC002635		
UNSPSC				

39121400



1424317

https://www.phoenixcontact.com/pc/products/1424317

## Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	323448a1-4b5c-4f8c-afd6-bf16f962fa4f

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com