

1424345
<https://www.phoenixcontact.com/pc/products/1424345>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing D15, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x M20, height: 56 mm, cable gland: none, Standard

Commercial data

Item number	1424345
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF7APE
Catalog page	Page 525 (C-2-2019)
GTIN	4055626370811
Weight per piece (including packing)	95.1 g
Weight per piece (excluding packing)	95.1 g
Customs tariff number	85389099
Country of origin	CN

HC-STA-D15-HLFS-1STM20-ELC-AL - Housing



1424345

<https://www.phoenixcontact.com/pc/products/1424345>

Technical data


Notes

General	For contact inserts HC-D15, A10
---------	---------------------------------

Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Product family	HC-STA-D
Application	Standard
Type	D15
No. of cable outlets	1
Type of the screw connection	1x M20
Type	Low design
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	30 mm
Height	56 mm
Length	63.5 mm

Material specifications

Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated

Mechanical properties

Mechanical data

Type of the screw connection	1x M20
Locking type	Pin

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK08
Ambient temperature (operation)	-40 °C ... 125 °C

HC-STA-D15-HLFS-1STM20-ELC-AL - Housing


1424345

<https://www.phoenixcontact.com/pc/products/1424345>



Drawings

Dimensional drawing



Dimensional drawing

1424345

<https://www.phoenixcontact.com/pc/products/1424345>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1424345>

**DNV**
Approval ID: TAE000037S

**cUL Recognized**
Approval ID: E255026

**UL Recognized**
Approval ID: E255026

**EAC**
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

HC-STA-D15-HLFS-1STM20-ELC-AL - Housing



1424345

<https://www.phoenixcontact.com/pc/products/1424345>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

1424345

<https://www.phoenixcontact.com/pc/products/1424345>

Accessories

G-INS-M20-S68N-NNES-S - Cable gland

1411163

<https://www.phoenixcontact.com/pc/products/1411163>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 6 mm ... 12 mm, shielding: no, connecting thread: M20 x 1.5, color: silver, with O-ring

G-INSEC-M20-S68N-NCRS-S - Cable gland

1411189

<https://www.phoenixcontact.com/pc/products/1411189>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 9 mm ... 13 mm, shielding: yes, connecting thread: M20 x 1.5, color: silver, with O-ring

HC-STA-D15-HLFS-1STM20-ELC-AL - Housing

1424345

<https://www.phoenixcontact.com/pc/products/1424345>



G-INS-M20-M68N-SNES-S - Cable gland

1424543

<https://www.phoenixcontact.com/pc/products/1424543>



Cable gland, material for screw connection: Stainless steel 1.4305, application: Standard, external cable diameter 6 mm ... 12 mm, shielding: no, connecting thread: M20 x 1.5, color: silver, with O-ring

HC-M-D15-MF-HB - Module carrier frame

1062122

<https://www.phoenixcontact.com/pc/products/1062122>



Module carrier frame, size: D15, 0.14 mm² ... 2.5 mm², application: Module carrier frame, for size D15 housings

HC-STA-D15-HLFS-1STM20-ELC-AL - Housing

1424345

<https://www.phoenixcontact.com/pc/products/1424345>



HC-D15-HCWS-PL-BK - Protective cover

1346521

<https://www.phoenixcontact.com/pc/products/1346521>

Protective cover D15, with single locking latch, protective cover material: PC, height: 19 mm, seal: no



US-EMLP (20X9) CUS - Plastic label

0830085

<https://www.phoenixcontact.com/pc/products/0830085>

Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



HC-STA-D15-HLFS-1STM20-ELC-AL - Housing



1424345

<https://www.phoenixcontact.com/pc/products/1424345>

US-EMLP-HA (20X9) - Plastic label

0830989

<https://www.phoenixcontact.com/pc/products/0830989>



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

WP-G HF IP66 M20 BK - Screw connection

3240898

<https://www.phoenixcontact.com/pc/products/3240898>



Cable gland, metric thread, IP66 protection, straight

HC-STA-D15-HLFS-1STM20-ELC-AL - Housing



1424345

<https://www.phoenixcontact.com/pc/products/1424345>

WP-G HF IP69K M20 BK - Screw connection

3240884

<https://www.phoenixcontact.com/pc/products/3240884>



Cable gland, metric thread, IP68/69k protection, straight

WP-GA HF IP66 M20 BK - Screw connection

3240926

<https://www.phoenixcontact.com/pc/products/3240926>



Cable gland, metric thread, IP66 protection, angled

HC-STA-D15-HLFS-1STM20-ELC-AL - Housing

1424345

<https://www.phoenixcontact.com/pc/products/1424345>



WP-GA HF IP69K M20 BK - Screw connection

3240912

<https://www.phoenixcontact.com/pc/products/3240912>

Cable gland, metric thread, IP68/69k protection, angled



WP-GR HF IP66 M20 BK - Screw connection

3240954

<https://www.phoenixcontact.com/pc/products/3240954>

Cable gland, metric thread, IP66 protection, with strain relief



HC-STA-D15-HLFS-1STM20-ELC-AL - Housing



1424345

<https://www.phoenixcontact.com/pc/products/1424345>

WP-GR HF IP69K M20 BK - Screw connection

3240940

<https://www.phoenixcontact.com/pc/products/3240940>



Cable gland, metric thread, IP68/69k protection, with strain relief

WP-G PP HF M20 - Screw connection

3240998

<https://www.phoenixcontact.com/pc/products/3240998>



Cable gland made from PP with metric thread, IP65 protection

HC-STA-D15-HLFS-1STM20-ELC-AL - Housing



1424345

<https://www.phoenixcontact.com/pc/products/1424345>

WP-GT PP HF M20 - Screw connection

3241012

<https://www.phoenixcontact.com/pc/products/3241012>

Cable gland made from PP with metric thread, rotatable, IP54 protection



WP-G BRASS IP40 M20 - Screw connection

3241047

<https://www.phoenixcontact.com/pc/products/3241047>

Cable gland made from brass with metric thread, IP40 protection



HC-STA-D15-HLFS-1STM20-ELC-AL - Housing



1424345

<https://www.phoenixcontact.com/pc/products/1424345>

WP-GT BRASS M20 - Screw connection

3241033

<https://www.phoenixcontact.com/pc/products/3241033>

Cable gland made from brass with metric thread, rotatable, IP40 protection



WP-G BRASS IP65 M20 - Screw connection

3241061

<https://www.phoenixcontact.com/pc/products/3241061>

Cable gland made from brass with metric thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com