

HC-STA-D50-HHFD-1STM32-EL-AL - Housing



1424404

<https://www.phoenixcontact.com/pc/products/1424404>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing D50, for double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x M32, height: 80 mm, cable gland: none, Standard

Commercial data


Item number	1424404
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF7APE
Catalog page	Page 532 (C-2-2019)
GTIN	4055626371443
Weight per piece (including packing)	254.6 g
Weight per piece (excluding packing)	240 g
Customs tariff number	85389099
Country of origin	CN

Technical data

Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Product family	HC-STA-D
Application	Standard
Type	D50
No. of cable outlets	1
Type of the screw connection	1x M32
Type	Tall design
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	56 mm
Height	80 mm
Length	82 mm

Material specifications

Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated

Mechanical properties

Mechanical data

Type of the screw connection	1x M32
Locking type	Pin

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK08
Ambient temperature (operation)	-40 °C ... 125 °C

HC-STA-D50-HHFD-1STM32-EL-AL - Housing


1424404

<https://www.phoenixcontact.com/pc/products/1424404>



Drawings

Dimensional drawing



Dimensional drawing

HC-STA-D50-HHFD-1STM32-EL-AL - Housing



1424404

<https://www.phoenixcontact.com/pc/products/1424404>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1424404>

DNV

Approval ID: TAE000037S



cUL Recognized

Approval ID: E255026



UL Recognized

Approval ID: E255026



EAC

Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

HC-STA-D50-HHFD-1STM32-EL-AL - Housing



1424404

<https://www.phoenixcontact.com/pc/products/1424404>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

HC-STA-D50-HHFD-1STM32-EL-AL - Housing



1424404

<https://www.phoenixcontact.com/pc/products/1424404>

Accessories

G-INS-M32-M68N-NNES-S - Cable gland

1411166

<https://www.phoenixcontact.com/pc/products/1411166>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

G-INS-M32-S68N-NNES-S - Cable gland

1424528

<https://www.phoenixcontact.com/pc/products/1424528>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 13 mm ... 18 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-STA-D50-HHFD-1STM32-EL-AL - Housing

1424404

<https://www.phoenixcontact.com/pc/products/1424404>



G-INSEC-M32-M68N-NCRS-S - Cable gland

1411191

<https://www.phoenixcontact.com/pc/products/1411191>



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 14 mm ... 21 mm, shielding: yes, connecting thread: M32 x 1.5, color: silver, with O-ring

G-INS-M32-M68N-SNES-S - Cable gland

1424545

<https://www.phoenixcontact.com/pc/products/1424545>



Cable gland, material for screw connection: Stainless steel 1.4305, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-STA-D50-HHFD-1STM32-EL-AL - Housing

1424404

<https://www.phoenixcontact.com/pc/products/1424404>



HC-D50-HCWD-PLR-BK - Protective cover

1346553

<https://www.phoenixcontact.com/pc/products/1346553>

Protective cover D50, with double locking latch, protective cover material: PC, height: 29 mm, seal: yes



US-EMLP (20X9) CUS - Plastic label

0830085

<https://www.phoenixcontact.com/pc/products/0830085>

Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



HC-STA-D50-HHFD-1STM32-EL-AL - Housing

1424404

<https://www.phoenixcontact.com/pc/products/1424404>



US-EMLP-HA (20X9) - Plastic label

0830989

<https://www.phoenixcontact.com/pc/products/0830989>



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

WP-G HF IP66 M32 BK - Screw connection

3240900

<https://www.phoenixcontact.com/pc/products/3240900>



Cable gland, metric thread, IP66 protection, straight

HC-STA-D50-HHFD-1STM32-EL-AL - Housing

1424404

<https://www.phoenixcontact.com/pc/products/1424404>



WP-G HF IP69K M32 BK - Screw connection

3240886

<https://www.phoenixcontact.com/pc/products/3240886>

Cable gland, metric thread, IP68/69k protection, straight



WP-GA HF IP66 M32 BK - Screw connection

3240928

<https://www.phoenixcontact.com/pc/products/3240928>

Cable gland, metric thread, IP66 protection, angled



HC-STA-D50-HHFD-1STM32-EL-AL - Housing

1424404

<https://www.phoenixcontact.com/pc/products/1424404>



WP-GA HF IP69K M32 BK - Screw connection

3240914

<https://www.phoenixcontact.com/pc/products/3240914>

Cable gland, metric thread, IP68/69k protection, angled



WP-GR HF IP66 M32 BK - Screw connection

3240956

<https://www.phoenixcontact.com/pc/products/3240956>

Cable gland, metric thread, IP66 protection, with strain relief



HC-STA-D50-HHFD-1STM32-EL-AL - Housing

1424404

<https://www.phoenixcontact.com/pc/products/1424404>



WP-GR HF IP69K M32 BK - Screw connection

3240942

<https://www.phoenixcontact.com/pc/products/3240942>



Cable gland, metric thread, IP68/69k protection, with strain relief

WP-G PP HF M32 - Screw connection

3241000

<https://www.phoenixcontact.com/pc/products/3241000>



Cable gland made from PP with metric thread, IP65 protection

HC-STA-D50-HHFD-1STM32-EL-AL - Housing



1424404

<https://www.phoenixcontact.com/pc/products/1424404>

WP-GT PP HF M32 - Screw connection

3241014

<https://www.phoenixcontact.com/pc/products/3241014>



Cable gland made from PP with metric thread, rotatable, IP54 protection

WP-G BRASS IP40 M32 - Screw connection

3241049

<https://www.phoenixcontact.com/pc/products/3241049>



Cable gland made from brass with metric thread, IP40 protection

HC-STA-D50-HHFD-1STM32-EL-AL - Housing



1424404

<https://www.phoenixcontact.com/pc/products/1424404>

WP-GT BRASS M32 - Screw connection

3241035

<https://www.phoenixcontact.com/pc/products/3241035>

Cable gland made from brass with metric thread, rotatable, IP40 protection



WP-G BRASS IP65 M32 - Screw connection

3241063

<https://www.phoenixcontact.com/pc/products/3241063>

Cable gland made from brass with metric thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com