

# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing



1424639

<https://www.phoenixcontact.com/us/products/1424639>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing D7, with screw locking, material: Zinc die-cast, cable outlets: 1, straight, 1x M25, height: 60 mm, cable gland: none, protective cover: no, Railway applications, for increased environmental and EMC requirements, Series HPR

## Your advantages

- Vibration and shock: IEC 61373/EN 50155, category 1, class 1B

## Commercial data

Item number	1424639
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF60
Product key	BF7AAJ
GTIN	4055626375687
Weight per piece (including packing)	87.5 g
Weight per piece (excluding packing)	87.5 g
Customs tariff number	85389099
Country of origin	CN

# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing



1424639

<https://www.phoenixcontact.com/us/products/1424639>

## Technical data

### Notes

General	for contact insertsHC-D7, D8, A3, A4, HS2-D7,Q5, Q7, Q12
---------	--

### Product properties

Product type	Housing with screw locking
Housing type	Sleeve housing
Series	HPR-D7
Application	Railway applications
Type	D7
No. of cable outlets	1
Type of the screw connection	1x M25
Type	Tall design
Protective cover	no
Shielded	yes
Cable outlet	straight
Pg screw connection	none

### Connection data

Tightening torque	1 Nm (Locking screw)
-------------------	----------------------

### Dimensions

Dimensional drawing	
Width	32.4 mm
Height	60 mm
Length	45.5 mm

### Material specifications

Housing material	Zinc die-cast
Housing surface material	Powder-coated, black
Locking latch material	Stainless steel

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66 (with sealing screw) IP68 (0.4 bar / 30 min. with sealing screw) IP69 ()
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

1424639

<https://www.phoenixcontact.com/us/products/1424639>

Mechanical properties

Mechanical data

Type of the screw connection	1x M25
Locking type	Screw

Mounting

Assembly note	M4 locking screw, slotted hexagon head screw (wrench size 7), tightening torque: 1 Nm
	Mount contact insert with sealing screw in the housing

# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing




1424639

<https://www.phoenixcontact.com/us/products/1424639>

## Drawings

Dimensional drawing



Dimensional drawing

1424639

<https://www.phoenixcontact.com/us/products/1424639>

## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1424639>

### DNV

Approval ID: TAE000037S



### EAC

Approval ID: RU C-DE.BL08.B.00511

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing



1424639

<https://www.phoenixcontact.com/us/products/1424639>

## Accessories

### G-INS-M25-M68N-NNES-S - Cable gland

1411165

<https://www.phoenixcontact.com/us/products/1411165>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 11 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with O-ring

---

### US-EMLP-HA (20X9) - Plastic label

0830989

<https://www.phoenixcontact.com/us/products/0830989>



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70



# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing

1424639

<https://www.phoenixcontact.com/us/products/1424639>



## US-EMLP-HA (20X9) CUS - Plastic label

0830995

<https://www.phoenixcontact.com/us/products/0830995>

Plastic label, Card, white, labeled, can be labeled with: THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70



---

## WP-G HF IP66 M25 BK - Screw connection

3240899

<https://www.phoenixcontact.com/us/products/3240899>

Cable gland, metric thread, IP66 protection, straight



# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing

1424639

<https://www.phoenixcontact.com/us/products/1424639>



## WP-G HF IP69K M25 BK - Screw connection

3240885

<https://www.phoenixcontact.com/us/products/3240885>

Cable gland, metric thread, IP68/69k protection, straight



---

## WP-GA HF IP66 M25 BK - Screw connection

3240927

<https://www.phoenixcontact.com/us/products/3240927>

Cable gland, metric thread, IP66 protection, angled



# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing

1424639

<https://www.phoenixcontact.com/us/products/1424639>



## WP-GA HF IP69K M25 BK - Screw connection

3240913

<https://www.phoenixcontact.com/us/products/3240913>

Cable gland, metric thread, IP68/69k protection, angled



---

## WP-GR HF IP66 M25 BK - Screw connection

3240955

<https://www.phoenixcontact.com/us/products/3240955>

Cable gland, metric thread, IP66 protection, with strain relief



# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing

1424639

<https://www.phoenixcontact.com/us/products/1424639>



## WP-GR HF IP69K M25 BK - Screw connection

3240941

<https://www.phoenixcontact.com/us/products/3240941>



Cable gland, metric thread, IP68/69k protection, with strain relief

---

## WP-G PP HF M25 - Screw connection

3240999

<https://www.phoenixcontact.com/us/products/3240999>



Cable gland made from PP with metric thread, IP65 protection

# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing



1424639

<https://www.phoenixcontact.com/us/products/1424639>

## WP-GT PP HF M25 - Screw connection

3241013

<https://www.phoenixcontact.com/us/products/3241013>



Cable gland made from PP with metric thread, rotatable, IP54 protection

---

## WP-G BRASS IP40 M25 - Screw connection

3241048

<https://www.phoenixcontact.com/us/products/3241048>



Cable gland made from brass with metric thread, IP40 protection

# HC-HPR-D07-HHWH-1TTM25-EM-BK - Housing



1424639

<https://www.phoenixcontact.com/us/products/1424639>

## WP-GT BRASS M25 - Screw connection

3241034

<https://www.phoenixcontact.com/us/products/3241034>

Cable gland made from brass with metric thread, rotatable, IP40 protection



---

## WP-G BRASS IP65 M25 - Screw connection

3241062

<https://www.phoenixcontact.com/us/products/3241062>

Cable gland made from brass with metric thread, IP65 protection



---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)