

SAC-5PT-FB/MB-MBF PBDP SH - T distributor



1424713

<https://www.phoenixcontact.com/no/products/1424713>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



T distributor, PROFIBUS DP (12 Mbps), 5-position, Socket straight M12, coding: B, on Plug straight M12, coding: B and Plug straight M12, coding: B, Fixed M12 thread on plug input

Your advantages

- Safe use in the field, thanks to a high degree of protection
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

Commercial data

Item number	1424713
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	31BBFS
Product key	BF1GAA
Catalog page	Page 436 (C-2-2019)
GTIN	4055626376769
Weight per piece (including packing)	50.3 g
Weight per piece (excluding packing)	50.3 g
Customs tariff number	85366990
Country of origin	DE

SAC-5PT-FB/MB-MBF PBDP SH - T distributor



1424713

<https://www.phoenixcontact.com/no/products/1424713>

Technical data

Product properties

Product type	T-distributor
Sensor type	PROFIBUS DP
Number of positions	5
No. of cable outlets	2
Shielded	yes
Coding	B
	B
Thread type	M12

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Electrical properties

Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	1 A (Contact 2 and 4)
	4 A (Contact 1 and 3)
Transmission medium	Copper


Interfaces

Signal type/category	PROFIBUS DP, 12 Mbps
----------------------	----------------------

Signaling

Status display	No
Status display present	No

Dimensions

Dimensional drawing	
Height	18 mm
Length	66.5 mm

Material specifications

Material	PBT
	PA
Flammability rating according to UL 94	V0
Seal material	NBR

SAC-5PT-FB/MB-MBF PBDP SH - T distributor



1424713

<https://www.phoenixcontact.com/no/products/1424713>

Material of grip body	PBT
Contact material	CuZn (pin) / CuSn (socket)
Contact surface material	Ni/Au
Material for screw connection	Zinc die-cast, nickel-plated

Connector

Connection 1

Type	Socket straight M12
Coding type	B

Connection 2

Type	Plug straight M12
Coding type	B

Connection 3

Type	Plug straight M12
Coding type	B

Cable/line

Signal type/category	PROFIBUS DP, 12 Mbps
----------------------	----------------------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions


Degree of protection	IP65
Ambient temperature (operation)	-25 °C ... 85 °C (Plug / socket)

Standards and regulations

Standard designation	M12 connector
Standards/specifications	according to IEC 61076-2-101

Drawings

Schematic diagram




Pin assignment M12 male connector, 5-pos., B-coded, male side

SAC-5PT-FB/MB-MBF PBDP SH - T distributor


1424713

<https://www.phoenixcontact.com/no/products/1424713>



M12 T distributor

Schematic diagram




Pin assignment M12 socket, 5-pos., B-coded, female side

1424713

<https://www.phoenixcontact.com/no/products/1424713>

Circuit diagram



SAC-5PT-FB/MB-MBF PBDP SH - T distributor



1424713

<https://www.phoenixcontact.com/no/products/1424713>

Classifications

ECLASS

ECLASS-11.0	27440106
ECLASS-12.0	27440106
ECLASS-13.0	27440106

ETIM

ETIM 9.0	EC002925
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------



1424713

<https://www.phoenixcontact.com/no/products/1424713>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT AS
Strømsveien 344
N-1081 Oslo
+47 22 07 68 00
norge@phoenixcontact.com