

1434950

https://www.phoenixcontact.com/us/products/1434950

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug angled M12 SPEEDCON, coding: A, on Valve connector A, with 1 LED, Wiring: Z diode, cable length: 1.5 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- · Save time, thanks to installation with SPEEDCON fast locking system
- · Convenient: increased machine availability thanks to guick and easy diagnostics
- · Our standard: robust halogen-free PUR cable

Commercial data

Item number	1434950
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF07
Product key	BF1DJA
Catalog page	Page 228 (C-2-2019)
GTIN	4046356413343
Weight per piece (including packing)	82.5 g
Weight per piece (excluding packing)	79.7 g
Customs tariff number	85444290
Country of origin	PL



1434950

https://www.phoenixcontact.com/us/products/1434950

Technical data

Product properties

Product type	Sensor/actuator cable with valve connector	
Application	Standard	
Number of positions	3	
No. of cable outlets	1	
Shielded	no	
Coding	A	
Insulation characteristics		
Overvoltage category	III	
Degree of pollution	3	

Material specifications

Flammability rating according to UL 94	НВ
Seal material	TPU
Material housing valve plug	TPU
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Contact material	CuSn
Valve plug contact insert material	PA 6.6
Contact surface material	Sn
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Insulation resistance	≥ 100 MΩ
Nominal voltage U _N	24 V AC
	24 V DC
Nominal current I _N	4 A

Valve connector characteristics

Fixing screws	M3 x 29
Pulse power	40 W (at 100 μs square-wave pulse)
Terminal voltage	70 V (at 2 mA constant current)
Reverse voltage	50 V

Mechanical properties

Mechanical	data
Mechanicai	uala

Insertion/withdrawal cycles	≥ 100 (M12 connector)	

Signaling

 ·-·····9	
Status display	1 LED



1434950

https://www.phoenixcontact.com/us/products/1434950

Status display present	Yes
nnector	
micetoi	
Connection 1	
Туре	Plug angled M12 SPEEDCON
Number of positions	3
Locking type	SPEEDCON
Coding type	A
Connection 2	
Type	Valve connector A
Material	CuSn (Contact)
	CuSn (Contact) Sn (Contact surface)
	CuSn (Contact)
	CuSn (Contact) Sn (Contact surface) PA 6.6 (Contact carriers)
	CuSn (Contact) Sn (Contact surface) PA 6.6 (Contact carriers)

PUR halogen-free black [PUR]

Dimensional drawing



Cable weight	30 kg/km
UL AWM Style	20549
Number of positions	3
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	28x 0.15 mm
AWG signal line	20
Conductor cross section	3x 0.5 mm²
Wire diameter incl. insulation	1.5 mm ±0.05 mm (Signal line)
External cable diameter	4.50 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	black 1, black 2, green/yellow
Overall twist	3 wires, twisted



1434950

https://www.phoenixcontact.com/us/products/1434950

Max. conductor resistance	39 Ω/km (at 20 °C)
Insulation resistance	min. 20 MΩ*km
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 1200 V
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	22.5 mm
Smallest bending radius, movable installation	45 mm
Max. bending cycles	15000000
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	according to DIN VDE 0482
	According to DIN EN 50265-2-1
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	largely oil-resistant
	partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Ambient temperature (operation)	-40 °C 80 °C (cable, fixed installation)
	-20 °C 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

7.11.11.11.11.11.11.11.11.11.11.11.11.11	
Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C 90 °C (Plug / socket)
	-20 °C 85 °C (valve plug)

Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101
Standard designation	Valve connector
Standards/specifications	EN 175301-803

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com