

SAC-5P- 3,0-PUR/AD-2L - Sensor/actuator cable



1435098

<https://www.phoenixcontact.com/us/products/1435098>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Valve connector AD (pressure switch), with 2 LEDs, cable length: 3 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Our standard: robust halogen-free PUR cable

Commercial data

Item number	1435098
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF07
Product key	BF1DBA
Catalog page	Page 240 (C-2-2019)
GTIN	4046356413459
Weight per piece (including packing)	162.5 g
Weight per piece (excluding packing)	152.2 g
Customs tariff number	85444290
Country of origin	PL

SAC-5P- 3,0-PUR/AD-2L - Sensor/actuator cable



1435098

<https://www.phoenixcontact.com/us/products/1435098>

Technical data

Product properties

Product type	Sensor/actuator cable with valve connector
Number of positions	5
Application	Standard
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	V0
Seal material	TPU
Material housing valve plug	TPU
Contact material	CuSn
Contact surface material	Ag
Contact carrier material	PBT
Contact material	CuSn
Valve plug contact insert material	PA 6
Contact surface material	Sn

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	24 V DC
Nominal current I_N	4 A
Protective circuit	unwired

Valve connector characteristics

Fixing screws	M3 x 29
---------------	---------

Signaling

Status display	2 LEDs
Status display present	Yes

Connector

Connection 1

Type	free cable end
------	----------------

Connection 2

Type	Valve connector AD (pressure switch) CuSn (Contact)
------	--

SAC-5P- 3,0-PUR/AD-2L - Sensor/actuator cable



1435098


<https://www.phoenixcontact.com/us/products/1435098>

Material	Sn (Contact surface)
	PA 6 (Contact carriers)
	TPU (Housing)

Cable/line

Cable length	3 m
--------------	-----

PUR halogen-free black [PUR]

Dimensional drawing	
Cable weight	44.8 kg/km
UL AWM Style	20549
Number of positions	5
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	28x 0.15 mm
AWG signal line	20
Conductor cross section	5x 0.5 mm²
Wire diameter incl. insulation	1.5 mm ±0.05 mm (Signal line)
External cable diameter	5.30 mm ±0.02 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	black 1, black 2, black 3, black 4, green/yellow
Overall twist	5 cores, twisted
Max. conductor resistance	39 Ω/km (at 20 °C)
Insulation resistance	min. 20 MΩ*km
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 1200 V
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	26.5 mm
Smallest bending radius, movable installation	53 mm
Max. bending cycles	15000000
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	in accordance with DIN UL-Style 20549
Resistance to oil	in accordance with DIN EN 60811-2-1

SAC-5P- 3,0-PUR/AD-2L - Sensor/actuator cable



1435098

<https://www.phoenixcontact.com/us/products/1435098>

Other resistance	Highly resistant to acids, alkaline solutions and solvents
	hydrolysis and microbe resistant
	largely oil-resistant
	partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Special properties	Flexible cable conduit capable
	Silicone-free
	Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-20 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-20 °C ... 85 °C (valve plug)
	-40 °C ... 80 °C (cable, fixed installation)
	-15 °C ... 80 °C (Cable, flexible installation)

Standards and regulations

Valve connector

Standard designation	Valve connector
Standards/specifications	EN 175301-803

SAC-5P- 3,0-PUR/AD-2L - Sensor/actuator cable

1435098

<https://www.phoenixcontact.com/us/products/1435098>




Drawings

Dimensional drawing




Valve connector, type AD, side view

Circuit diagram




Schematic diagram



Valve plug connector pin assignment, type AD

Dimensional drawing



Valve connector, type AD

SAC-5P- 3,0-PUR/AD-2L - Sensor/actuator cable



1435098

<https://www.phoenixcontact.com/us/products/1435098>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1435098>

**EAC-RoHS**
Approval ID: RU D-DE.HB35.B.00387

	CSAus Approval ID: 13631			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	24 V	6 A	-	-

SAC-5P- 3,0-PUR/AD-2L - Sensor/actuator cable



1435098

<https://www.phoenixcontact.com/us/products/1435098>

Classifications

ECLASS

ECLASS-11.0	27060312
ECLASS-12.0	27060312
ECLASS-13.0	27060312

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SAC-5P- 3,0-PUR/AD-2L - Sensor/actuator cable



1435098

<https://www.phoenixcontact.com/us/products/1435098>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com