

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable

1435632

<https://www.phoenixcontact.com/pc/products/1435632>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug angled M12 SPEEDCON, coding: A, with 1 LED, on Valve connector CI (9.4 mm), with 1 LED, Wiring: Z diode, cable length: 0.3 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Save time, thanks to installation with SPEEDCON fast locking system
- Convenient: increased machine availability thanks to quick and easy diagnostics
- Our standard: robust halogen-free PUR cable

Commercial data

Item number	1435632
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF1DOA
Catalog page	Page 228 (C-2-2019)
GTIN	4046356413886
Weight per piece (including packing)	34.6 g
Weight per piece (excluding packing)	32.2 g
Customs tariff number	85444290
Country of origin	PL

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable



1435632

<https://www.phoenixcontact.com/pc/products/1435632>

Technical data

Product properties

Product type	Sensor/actuator cable with valve connector
Application	Standard
Number of positions	3
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	TPU
Material housing valve plug	TPU
Material of grip body	TPU
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Contact material	CuSn
Valve plug contact insert material	PA 6.6
Contact surface material	Sn
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	24 V AC
	24 V DC
Nominal current I_N	4 A

Valve connector characteristics

Fixing screws	M3 x 29
Pulse power	40 W (at 100 μ s square-wave pulse)
Terminal voltage	70 V (at 2 mA constant current)
Reverse voltage	50 V

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100 (M12 connector)
-----------------------------	----------------------------

Signaling

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable



1435632

<https://www.phoenixcontact.com/pc/products/1435632>

Status display	1 LED
Status display present	Yes

Connector

Connection 1

Type	Plug angled M12 SPEEDCON
Number of positions	3
Locking type	SPEEDCON
Coding type	A


Connection 2

Type	Valve connector CI (9.4 mm)
Number of positions	3
Material	CuSn (Contact)
	Sn (Contact surface)
	PA 6.6 (Contact carriers)
	TPU (Housing)

Cable/line

Cable length	0.3 m
--------------	-------

PUR halogen-free black [PUR]

Dimensional drawing	
Cable weight	30 kg/km
UL AWM Style	20549
Number of positions	3
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	28x 0.15 mm
AWG signal line	20
Conductor cross section	3x 0.5 mm²
Wire diameter incl. insulation	1.5 mm ±0.05 mm (Signal line)
External cable diameter	4.50 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable



1435632

<https://www.phoenixcontact.com/pc/products/1435632>

Single wire, color	black 1, black 2, green/yellow
Overall twist	3 wires, twisted
Max. conductor resistance	39 Ω /km (at 20 °C)
Insulation resistance	min. 20 M Ω *km
Nominal voltage, cable	$\leq$ 300 V
Test voltage	$\geq$ 1200 V
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	22.5 mm
Smallest bending radius, movable installation	45 mm
Dynamic load capacity (bending)	Max. bending cycles: 15000000, Bending radius: 50 mm, Traversing path: 0.9 m, Traversing rate: 5 m/s, Acceleration: 30 m/s ²
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	according to DIN VDE 0482 According to DIN EN 50265-2-1
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	largely oil-resistant partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -20 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket) -20 °C ... 85 °C (valve plug) -40 °C ... 80 °C (cable, fixed installation) -15 °C ... 80 °C (Cable, flexible installation)

Standards and regulations

M12


Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable


1435632

<https://www.phoenixcontact.com/pc/products/1435632>

Drawings



Dimensional drawing




Valve connector, type CI, side view

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable

1435632


<https://www.phoenixcontact.com/pc/products/1435632>

Dimensional drawing



M12 x 1 male plug, angled

Dimensional drawing




Valve connector, type CI

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable

1435632


<https://www.phoenixcontact.com/pc/products/1435632>

Schematic diagram



Valve connector connector pin assignment, type CI

Schematic diagram



Pin assignment M12 plug, 3-pos., valve connector

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable



1435632
<https://www.phoenixcontact.com/pc/products/1435632>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1435632>



EAC-RoHS
Approval ID: RU D-DE.HB35.B.00387

	CSAus Approval ID: 13631			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	24 V	4 A	-	-

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable



1435632
<https://www.phoenixcontact.com/pc/products/1435632>

Classifications

ECLASS

ECLASS-11.0	27060312
ECLASS-12.0	27060312
ECLASS-13.0	27060312

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SAC-3P-MR/ 0,3-PUR/CI-1L-Z SCO - Sensor/actuator cable



1435632
<https://www.phoenixcontact.com/pc/products/1435632>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com