

1436521

https://www.phoenixcontact.com/us/products/1436521

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, Universal, 6-position, Pin, straight, M8, coding: A, Rear mounting, M8 x 1, Wave soldering

Your advantages

- · Easy PCB assembly: one-piece connectors for wave soldering
- · Standard pin assignments and codings for signal transmission with a uniform design-in design
- · For high transmission reliability: optional shield connection to the housing and latching on the PCB

Commercial data

Item number	1436521
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB22
Product key	ABQJAA
Catalog page	Page 226 (C-2-2013)
GTIN	4046356434881
Weight per piece (including packing)	5.625 g
Weight per piece (excluding packing)	5.07 g
Customs tariff number	85366990
Country of origin	DE



1436521

https://www.phoenixcontact.com/us/products/1436521

Technical data

Mounting

Mounting type	Rear mounting M8 x 1 With locking nut
Assembly instructions	With locking nut

Product properties

Product type	Circular connectors (device side)	
Sensor type	Universal	
Number of positions	6	
Shielded	no	
Coding	A	
Thread type	M8	
Insulation characteristics		
Overvoltage category	II	
Degree of pollution	3	

Material specifications

Flammability rating according to UL 94	НВ
Seal material	NBR
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Brass, nickel-plated

Electrical properties

Rated surge voltage	0.8 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U _N	30 V AC
	30 V DC
Nominal current I _N	2 A

Connection data

Conductor connection

Connection method	Wave soldering
Contact connection type	Pin
Tightening torque	1 Nm 1.5 Nm (Installation-side)

Connector

Connection 1



1436521

https://www.phoenixcontact.com/us/products/1436521

Head design	Pin		
Head cable outlet	straight		
Head thread type	M8		
Coding	A		
Cable/line			
Signal type/category	Universal		
Environmental and real-life conditions			
Ambient conditions			
	IP67		
Ambient conditions	IP67 IP67		
Ambient conditions			
Ambient conditions Degree of protection	IP67		
Ambient conditions Degree of protection Ambient temperature (operation)	IP67		
Ambient conditions Degree of protection Ambient temperature (operation) Standards and regulations	IP67 -40 °C 85 °C		




1436521

https://www.phoenixcontact.com/us/products/1436521

Drawings

Schematic diagram



Pin assignment M8 plug, 6-pos., view male side



1436521

https://www.phoenixcontact.com/us/products/1436521

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1436521

Approval ID: E221474-20070307					
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
		30 V	1.5 A	26 - 26	-

SU UL Recognized Approval ID: E221474-20	UL Recognized Approval ID: E221474-20070307			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	30 V	1.5 A	26 - 26	-

cULus Recognized



1436521

https://www.phoenixcontact.com/us/products/1436521

Classifications

ECLASS

	ECLASS-11.0	27440102
	ECLASS-12.0	27440116
	ECLASS-13.0	27440116
ΕT	IM	
	ETIM 9.0	EC002635
UN	SPSC	
	UNSPSC 21.0	39121400



1436521

https://www.phoenixcontact.com/us/products/1436521

Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com