


SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable



1438639

<https://www.phoenixcontact.com/us/products/1438639>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 5-position, PVC, black, free cable end, on Valve connector AD (pressure switch), with 2 LEDs, Wiring: unwired, cable length: 5 m

Commercial data

Item number	1438639
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF07
Product key	BF1DBA
Catalog page	Page 241 (C-2-2019)
GTIN	4046356488532
Weight per piece (including packing)	291.4 g
Weight per piece (excluding packing)	286.3 g
Customs tariff number	85444290
Country of origin	PL

SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable



1438639

<https://www.phoenixcontact.com/us/products/1438639>

Technical data

Product properties

Product type	Sensor/actuator cable with valve connector
Number of positions	5
Application	Standard
No. of cable outlets	1
Shielded	no

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	V0
Seal material	TPU
Material housing valve plug	TPU
Contact material	CuSn
Valve plug contact insert material	PA 6
Contact surface material	Sn

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	24 V DC
Nominal current I_N	4 A
Protective circuit	unwired

Valve connector characteristics

Fixing screws	M3 x 29
---------------	---------

Signaling

Status display	2 LEDs
Status display present	Yes

Connector

Connection 1

Type	free cable end
------	----------------

Connection 2

Type	Valve connector AD (pressure switch)
Material	CuSn (Contact)
	Sn (Contact surface)
	PA 6 (Contact carriers)
	TPU (Housing)

SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable




1438639

<https://www.phoenixcontact.com/us/products/1438639>

Cable/line

Cable length	5 m
--------------	-----

PVC black [PVC]

Dimensional drawing	
Cable weight	58.7 kg/km
UL AWM Style	2464
Number of positions	5
Shielded	no
Cable type	PVC black [PVC]
Conductor structure signal line	16x 0.20 mm
AWG signal line	20
Conductor cross section	5x 0.5 mm²
Wire diameter incl. insulation	1.5 mm ±0.05 mm
External cable diameter	5.60 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	black
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	black 1, black 2, black 3, black 4, green/yellow
Overall twist	5 cores, twisted
Max. conductor resistance	39 Ω/km (at 20 °C)
Insulation resistance	≥ 20 MΩ*km
Nominal voltage, cable	300 V
Test voltage	1200 V
Minimum bending radius, fixed installation	5 x D
Smallest bending radius, fixed installation	28 mm
Flame resistance	DIN VDE 0482 DIN EN 50265-2-1
Resistance to oil	largely oil-resistant
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
----------------------	------

SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable



1438639

<https://www.phoenixcontact.com/us/products/1438639>

	IP67
Ambient temperature (operation)	-20 °C ... 85 °C (valve plug)

Standards and regulations

Valve connector	
Standard designation	Valve connector
Standards/specifications	EN 175301-803

SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable


1438639

<https://www.phoenixcontact.com/us/products/1438639>



Drawings

Schematic diagram




Valve plug connector pin assignment, type AD

SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable


1438639

<https://www.phoenixcontact.com/us/products/1438639>

Dimensional drawing




Valve connector, type AD



SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable

1438639

<https://www.phoenixcontact.com/us/products/1438639>



Valve connector, type AD, side view

SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable



1438639

<https://www.phoenixcontact.com/us/products/1438639>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1438639>



EAC-RoHS
Approval ID: RU D-DE.HB35.B.00387

	CSAus Approval ID: 13631			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	24 V	6 A	-	-

SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable



1438639

<https://www.phoenixcontact.com/us/products/1438639>

Classifications

ECLASS

ECLASS-11.0	27060312
ECLASS-12.0	27060312
ECLASS-13.0	27060312

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SAC-5P- 5,0-PVC/AD-2L - Sensor/actuator cable



1438639

<https://www.phoenixcontact.com/us/products/1438639>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com