

SAC-3P-MR/10,0-PUR/BI-1L-Z SCO - Sensor/actuator cable



1438914
<https://www.phoenixcontact.com/us/products/1438914>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug angled M12 SPEEDCON, on Valve connector BI (11 mm), with 1 LED, Wiring: Z diode, cable length: 10 m

Commercial data

Item number	1438914
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF07
Product key	BF1DMA
GTIN	4046356496766
Weight per piece (including packing)	327.2 g
Weight per piece (excluding packing)	327.2 g
Customs tariff number	85444290
Country of origin	PL

SAC-3P-MR/10,0-PUR/BI-1L-Z SCO - Sensor/actuator cable



1438914

<https://www.phoenixcontact.com/us/products/1438914>

Technical data

Product properties

Product type	Sensor/actuator cable with valve connector
Number of positions	3

Electrical properties

Nominal voltage U_N	24 V AC
	24 V DC

Connector

Connection 1

Type	Plug angled M12 SPEEDCON
Number of positions	3
Locking type	SPEEDCON


Connection 2

Type	Valve connector BI (11 mm)
Number of positions	3

Cable/line

Cable length	10 m
--------------	------

PUR halogen-free black [PUR]

Dimensional drawing	
Cable weight	30 kg/km
UL AWM Style	20549
Number of positions	3
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	28x 0.15 mm
AWG signal line	20
Conductor cross section	3x 0.5 mm ²
Wire diameter incl. insulation	1.5 mm ±0.05 mm (Signal line)
External cable diameter	4.50 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021

SAC-3P-MR/10,0-PUR/BI-1L-Z SCO - Sensor/actuator cable



1438914

<https://www.phoenixcontact.com/us/products/1438914>

Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	black 1, black 2, green/yellow
Overall twist	3 wires, twisted
Max. conductor resistance	39 Ω /km (at 20 °C)
Insulation resistance	min. 20 M Ω *km
Nominal voltage, cable	$\leq$ 300 V
Test voltage	$\geq$ 1200 V
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	22.5 mm
Smallest bending radius, movable installation	45 mm
Max. bending cycles	15000000
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	according to DIN VDE 0482 According to DIN EN 50265-2-1
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	largely oil-resistant partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -20 °C ... 80 °C (Cable, flexible installation)

SAC-3P-MR/10,0-PUR/BI-1L-Z SCO - Sensor/actuator cable



1438914
<https://www.phoenixcontact.com/us/products/1438914>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1438914>



EAC-RoHS
Approval ID: RU D-DE.HB35.B.00387

	CSAus Approval ID: 13631			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	24 V	4 A	-	-

SAC-3P-MR/10,0-PUR/BI-1L-Z SCO - Sensor/actuator cable



1438914
<https://www.phoenixcontact.com/us/products/1438914>

Classifications

ECLASS

ECLASS-11.0	27060312
ECLASS-12.0	27060312
ECLASS-13.0	27060312

ETIM

ETIM 8.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SAC-3P-MR/10,0-PUR/BI-1L-Z SCO - Sensor/actuator cable



1438914

<https://www.phoenixcontact.com/us/products/1438914>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

SAC-3P-MR/10,0-PUR/BI-1L-Z SCO - Sensor/actuator cable



1438914

<https://www.phoenixcontact.com/us/products/1438914>

Accessories

SAC-V-SCREW-M3-29 KNURL - Screw

1403779

<https://www.phoenixcontact.com/us/products/1403779>

Fillister head screw with plastic knurl, M3 x 40



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com