### SACC-DSI-M12MS-17CON-M16 - Device connector rear mounting



1441846

https://www.phoenixcontact.com/us/products/1441846

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 17-position, Pin, straight, M12, coding: A, Rear mounting, M16 x 1.5, Solder pins, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0. 1 %) item no.: 1239743

#### Your advantages

- Easy PCB assembly: one-piece connectors for wave soldering
- · All standard pin assignments and codings for signal, data, and power transmission with a uniform design-in design
- · SPEEDCON fast locking system reduces cabling times

#### Commercial data

Item number	1441846
Packing unit	20 pc
Minimum order quantity	20 pc
Note	Made to order (non-returnable)
Sales key	AB26
Product key	ABQEGJ
Catalog page	Page 250 (C-2-2013)
GTIN	4046356534048
Weight per piece (including packing)	16.5 g
Weight per piece (excluding packing)	16.5 g
Customs tariff number	85366990
Country of origin	DE

### SACC-DSI-M12MS-17CON-M16 - Device connector rear mounting



1441846

https://www.phoenixcontact.com/us/products/1441846

#### Technical data

#### Notes

General	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
General	Lock nut is included in the scope of delivery

#### Mounting

Mounting type	Rear mounting M16 x 1.5 With flat nut
Assembly instructions	With flat nut

#### Product properties

Product type	Circular connectors (device side)
Number of positions	17
Shielded	no
Coding	A
Thread type	M12
Insulation characteristics	
Overveltore esterony	II.

Over voltage category	"
Degree of pollution	3

#### **Dimensions**

Length of the solder pin	6 mm
	6 mm

### Material specifications

Flammability rating according to UL 94	V0
Seal material	NBR
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated

#### Electrical properties

Rated surge voltage	0.8 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U <sub>N</sub>	30 V
Nominal current I <sub>N</sub>	1.5 A

# SACC-DSI-M12MS-17CON-M16 - Device connector rear mounting



1441846

https://www.phoenixcontact.com/us/products/1441846

#### Connection data

#### Conductor connection

Connection method	Solder pins
Contact connection type	Pin
Tightening torque	3 Nm 4 Nm (Installation-side)

#### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	> 100

#### Connector

#### Connection 1

Head design	Pin
Head cable outlet	straight
Head thread type	M12
Coding	A

#### Cable/line

Ambient temperature (operation)	-40 °C 85 °C (cable, fixed installation)
	-25 °C 85 °C (Cable, flexible installation)

#### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP67 (When plugged in)
	IP65 (When plugged in)
	IP65/IP67
Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)
	-40 °C 85 °C (without mechanical actuation)
	-25 °C 85 °C (Cable, flexible installation)
	-40 °C 85 °C (cable, fixed installation)

#### Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

## SACC-DSI-M12MS-17CON-M16 - Device connector rear mounting



1441846

https://www.phoenixcontact.com/us/products/1441846

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com