

## Power cable - SAC-5P-MINMR/1,0-430/MINFR PWR - 1443475

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power cable, 5-position, PVC, gray RAL 7001, Plug angled 7/8"-16UNF, on Socket angled 7/8"-16UNF, cable length: 1 m, 1.5 mm<sup>2</sup> conductor cross section, For power supply

### Why buy this product

- ✓ Easy and safe: 100% electrically tested plug-in components
- ✓ Robust connectors in size 7/8"-16UNF
- ✓ High-performance: connectors and cables with a large conductor cross section for power supply

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 STK                                                                                                   |
| GTIN         | <br>4 046356 537032 |
| GTIN         | 4046356537032                                                                                           |

### Technical data

#### Dimensions

|                 |     |
|-----------------|-----|
| Length of cable | 1 m |
|-----------------|-----|

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -40 °C ... 90 °C (Plug / socket) |
| Degree of protection            | IP65                             |
|                                 | IP67                             |
|                                 | IP68                             |

#### General

|                       |          |
|-----------------------|----------|
| Rated current at 40°C | 10 A     |
| Rated voltage         | 600 V AC |
|                       | 600 V DC |
| Rated surge voltage   | 4000 V   |
| Number of positions   | 5        |

# Power cable - SAC-5P-MINMR/1,0-430/MINFR PWR - 1443475

## Technical data

### General

|                                                                             |                           |
|-----------------------------------------------------------------------------|---------------------------|
| Color handle area                                                           | black                     |
| Insulation resistance                                                       | $\geq 10 \text{ M}\Omega$ |
| Coding                                                                      | A - standard              |
| Status display                                                              | No                        |
| Protective circuit/component                                                | Unwired                   |
| Overvoltage category                                                        | II                        |
| Degree of pollution                                                         | 3                         |
| Structure of individual litz in acc. with VDE 0295 / smallest wire diameter | VDE 0295 class 5          |
| Insertion/withdrawal cycles                                                 | 100                       |

### Material

|                                        |                              |
|----------------------------------------|------------------------------|
| Flammability rating according to UL 94 | HB                           |
| Contact material                       | CuZn                         |
| Contact surface material               | AU                           |
| Contact carrier material               | PA 6.6                       |
| Material of grip body                  | TPU                          |
| Material, knurls                       | Zinc die-cast, nickel-plated |

### Standards and Regulations

|                                        |                                  |
|----------------------------------------|----------------------------------|
| Flame resistance                       | UL 1581, Sec. 1061 (Cable Flame) |
|                                        | IEC 60332-1-2                    |
| Flammability rating according to UL 94 | HB                               |

### Cable

|                                               |                                                  |
|-----------------------------------------------|--------------------------------------------------|
| Cable type                                    | PVC gray                                         |
| Cable type (abbreviation)                     | 430                                              |
| UL AWM style                                  | 21098 (90 °C / 600 V)                            |
| Conductor cross section                       | 5x 1.5 mm <sup>2</sup>                           |
| AWG signal line                               | 16                                               |
| Conductor structure, voltage supply           | 30x 0.25 mm                                      |
| Wire colors                                   | Black 1, black 2, black 3, black 4, green/yellow |
| Overall twist                                 | 5 cores, twisted                                 |
| External sheath, color                        | gray RAL 7001                                    |
| External cable diameter D                     | 10 mm                                            |
| Minimum bending radius, fixed installation    | 4 x D                                            |
| Minimum bending radius, flexible installation | 12.5 x D                                         |
| Cable weight                                  | 168 kg/km                                        |
| Outer sheath, material                        | PVC                                              |
| Material conductor insulation                 | PVC                                              |
| Conductor material                            | Bare Cu litz wires                               |
| Nominal voltage, cable                        | 600 V                                            |
| Test voltage, cable                           | 3000 V                                           |

# Power cable - SAC-5P-MINMR/1,0-430/MINFR PWR - 1443475

## Technical data

### Cable


|                                 |                                                |
|---------------------------------|------------------------------------------------|
| Flame resistance                | UL 1581, Sec. 1061 (Cable Flame)               |
|                                 | IEC 60332-1-2                                  |
| Resistance to oil               | good oil-resistance                            |
| Ambient temperature (operation) | -40 °C ... 90 °C (cable, fixed installation)   |
|                                 | -5 °C ... 90 °C (cable, flexible installation) |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | DOTe 15571-58-1                                                                                     |
|            | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |


## Drawings

Schematic diagram




Pin assignment, plug, 7/8"-16UNF, 5-pos., view of male side

Schematic diagram




Pin assignment, socket, 7/8"-16UNF, 5-pos., view of female side

Cable cross section



PVC gray [430]


Dimensional drawing



7/8"-16UNF plug, angled

## Power cable - SAC-5P-MINMR/1,0-430/MINFR PWR - 1443475

Dimensional drawing



Circuit diagram



Contact assignment of the 7/8" connector and the 7/8" socket

7/8"-16UNF socket, angled

### Approvals

Approvals

Approvals

EAC

Ex Approvals

### Approval details

EAC



EAC-Zulassung

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>