

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector front mounting, 5-position, Socket, straight, M12, coding: B, on free cable end, Front mounting, M20 x 1,5, Individual wires, cable length: 0.5 m, 0.34 mm<sup>2</sup>, TPE litz wire

## Your advantages

- Preassembled with litz wires for immediate use
- Customer-specific assemblies and litz wire lengths available
- Sealed on the litz wire side for optimum leak-tightness
- All standard pin assignments and codings for signal, data, and power transmission with a uniform design-in design
- For high transmission safety: shield connection to the housing with optional EMC nut

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1452097             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | AB24                |
| Product key                          | ABQCVC              |
| Catalog page                         | Page 269 (C-2-2013) |
| GTIN                                 | 4046356528702       |
| Weight per piece (including packing) | 36 g                |
| Weight per piece (excluding packing) | 36 g                |
| Customs tariff number                | 85444290            |
| Country of origin                    | DE                  |

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

## Technical data

### Notes

|                    |  |
|--------------------|--|
| Notes on operation | The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration. |
| General            | Contact connection method: Crimp connection  |

### Safety note

|             |  |
|-------------|--|
| Safety note | WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.   |
|             | <ul style="list-style-type: none"><li>• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.</li></ul>  |
|             | <ul style="list-style-type: none"><li>• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.</li></ul> |
|             | <ul style="list-style-type: none"><li>• The products are suitable for applications in plant, controller, and electrical device engineering.</li></ul>  |
|             | <ul style="list-style-type: none"><li>• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.</li></ul>   |
|             | <ul style="list-style-type: none"><li>• Assembled products may not be manipulated or improperly opened.</li></ul>  |
|             | <ul style="list-style-type: none"><li>• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a>).</li></ul>   |
|             | <ul style="list-style-type: none"><li>• When using the product in direct connection with third-party manufacturers, the user is responsible.</li></ul>   |
|             | <ul style="list-style-type: none"><li>• For operating voltages &gt; 50 V AC, conductive connector housings must be grounded</li></ul>  |
|             | <ul style="list-style-type: none"><li>• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.</li></ul>  |
|             | <ul style="list-style-type: none"><li>• Observe the corresponding technical data. You will find information:<ul style="list-style-type: none"><li>o On the product</li><li>o On the packing label</li><li>o In the supplied documentation</li><li>o Online at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a> under the product</li></ul></li></ul>  |
|             | <ul style="list-style-type: none"><li>• Only use tools recommended by Phoenix Contact</li></ul>  |
|             | <ul style="list-style-type: none"><li>• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory</li></ul>   |

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

|  |   |
|--|---|
|  | section of the product at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a>   |
|  | <ul style="list-style-type: none"><li>• Ensure that the protective or functional ground has been properly connected.</li><li>• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector</li><li>• The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).</li></ul> |

## Mounting

|               |                          |
|---------------|--------------------------|
| Mounting type | Front mounting M20 x 1,5 |
|---------------|--------------------------|

## Product properties

|                      |                                   |
|----------------------|-----------------------------------|
| Product type         | Circular connectors (device side) |
| Application          | Signal                            |
| Number of positions  | 5                                 |
| No. of cable outlets | 1                                 |
| Shielded             | no                                |
| Coding               | B                                 |
| Thread type          | M12                               |

## Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

## Material specifications

|  |                          |
|--|--------------------------|
| Flammability rating according to UL 94 | V0                       |
| Seal material                          | NBR                      |
| Contact material                       | CuZn                     |
| Contact surface material               | Au                       |
| Contact carrier material               | PA 6.6                   |
| Material for screw connection          | Stainless steel          |
| Conductor material                     | Tin-plated Cu litz wires |

## Electrical properties

|                           |           |
|---------------------------|-----------|
| Rated surge voltage       | 1.5 kV    |
| Contact resistance        | ≤ 3 mΩ    |
| Insulation resistance     | ≥ 100 MΩ  |
| Nominal voltage $U_N$     | 60 V      |
| Nominal current $I_N$     | 4 A       |
| Max. conductor resistance | 57.6 mΩ/m |

## Connection data

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

## Conductor connection

|                         |                                   |
|-------------------------|-----------------------------------|
| Connection method       | Individual wires                  |
| Contact connection type | Socket                            |
| Conductor cross section | 0.34 mm <sup>2</sup>              |
| Tightening torque       | 3 Nm ... 4 Nm (Installation-side) |

## Mechanical properties

### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | > 100 |
|-----------------------------|-------|

## Connector

### Connection 1

|                   |          |
|-------------------|----------|
| Head design       | Socket   |
| Head cable outlet | straight |
| Head thread type  | M12      |
| Coding            | B        |

### Connection 2

|             |                |
|-------------|----------------|
| Head design | free cable end |
|-------------|----------------|

## Cable/line

|                                 |   |
|---------------------------------|---|
| Cable length                    | 0.5 m   |
| Cable type                      | TPE litz wire   |
| Wire diameter incl. insulation  | 1.2 mm ±0.07 mm   |
| Single wire, color              | brown, white, blue, black, gray   |
| Cable cross section             | 0.34 mm <sup>2</sup>  |
| Conductor material              | Tin-plated Cu litz wires  |
| Conductor structure signal line | 7x 0.25 mm  |
| AWG signal line                 | 22  |
| Material wire insulation        | TPE   |
| Thickness, insulation           | 0.21 mm   |
| Nominal voltage, cable          | 300 V   |
| Test voltage, cable             | 2000 V AC   |
| Cable resistance                | ≤ 57.6 mΩ/m   |
| Cable insulation resistance     | ≥ 20 MΩ*km  |
| Ambient temperature (operation) | -40 °C ... 85 °C (cable, fixed installation)<br>-25 °C ... 85 °C (Cable, flexible installation) |

## Environmental and real-life conditions

### Ambient conditions

|                      |                      |
|----------------------|----------------------|
| Degree of protection | IP65/IP67/IP69/IP69K |
|----------------------|----------------------|

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

|                                 |   |
|---------------------------------|---|
|                                 | IP65/IP67/IP69K                                 |
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket)                |
|                                 | -40 °C ... 85 °C (without mechanical actuation) |
|                                 | -25 °C ... 85 °C (Cable, flexible installation) |
|                                 | -40 °C ... 85 °C (cable, fixed installation)    |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting

1452097


<https://www.phoenixcontact.com/us/products/1452097>

## Drawings

Circuit diagram



Schematic diagram



Pin assignment M12 socket, 5-pos., B-coded, female side


# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

Diagram



$I$  = current strength,  $T$  = ambient temperature

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1452097>

|  <b>cULus Recognized</b><br>Approval ID: E221474-20140616 |                       |                       |                   |                             |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|  | 60 V                  | 4 A                   | 22 - 20           | -                           |

|  <b>cUL Recognized</b><br>Approval ID: E118976-20100522 |                       |                       |                   |                             |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|  | 60 V                  | 4 A                   | 22 - 22           | -                           |

|  <b>UL Recognized</b><br>Approval ID: E118976-20100522 |                       |                       |                   |                             |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
|   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|   | 60 V                  | 4 A                   | 22 - 22           | -                           |

| <b>cULus Recognized</b> |  |  |  |  |
|-------------------------|--|--|--|--|
|-------------------------|--|--|--|--|

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

## Accessories

### PROT-M12 - Screw plug

1680539

<https://www.phoenixcontact.com/us/products/1680539>



An M12 screw plug for the unoccupied M12 sockets of the sensor/actuator cable, boxes and flush-type connectors

---

### PROT-M12 SH - Screw plug

1503302

<https://www.phoenixcontact.com/us/products/1503302>



An M12 screw plug for the unoccupied M12 sockets of the shielded sensor/actuator cable, boxes and flush-type connectors

# SACC-E-M12FSB-5CON-M20/0,5 VA - Device connector front mounting



1452097

<https://www.phoenixcontact.com/us/products/1452097>

## PROT-M12 FB - Screw plug

1555538

<https://www.phoenixcontact.com/us/products/1555538>



M12 high-grade steel screw plug, for unoccupied M12 sockets of the sensor/actuator cables, boxes and flush-type connectors for the food industry

---

## A-INL-M20-S-S - Counter nut

1411249

<https://www.phoenixcontact.com/us/products/1411249>



Counter nut, for threads M20 x 1.5, color: silver

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)