

SACB-4/ 4-L-C GG SCO P - Distributor box header



1452864

<https://www.phoenixcontact.com/pc/products/1452864>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Distributor box header, application: Standard, connection method: M12-SPEEDCON-socket Plastic, number of slots: 4, number of positions: 4, coding: A, slot assignment: single, status display: Yes, pnp; master cable connection: Pluggable screw connection, shielding: no

Commercial data

Item number	1452864
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF3CBD
Catalog page	Page 263 (C-2-2019)
GTIN	4046356553728
Weight per piece (including packing)	124.1 g
Weight per piece (excluding packing)	121 g
Customs tariff number	85366990
Country of origin	DE

SACB-4/ 4-L-C GG SCO P - Distributor box header



1452864

<https://www.phoenixcontact.com/pc/products/1452864>

Technical data

Notes

General	NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.
General	Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories".

Product properties

Product type	Header with metric measurement slots
Application	Standard
Number of positions	4
Number of slots	4
Coding	A
LED	yes

System properties

Local diagnostics	
Monitored function	Supply voltage
Optical representation	Green LED

Electrical properties

Max. operating voltage U_{max}	30 V DC
Local diagnostics	Supply voltage Green LED
	Status display I/O Yellow LED
Nominal voltage U_N	24 V DC
Rated current, total	10 A
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	4 A

Signaling

Status display present	Yes
------------------------	-----

Dimensions

Dimensional drawing	
---------------------	--

SACB-4/ 4-L-C GG SCO P - Distributor box header



1452864

<https://www.phoenixcontact.com/pc/products/1452864>

Width	54 mm
Height	19 mm
Length	117 mm

Material specifications

Material Threaded sleeve	PBT
Material Housing	PBT
Material Molding compound	PUR
Flammability rating according to UL 94	V0
Seal material O-ring	NBR
Contact material	Cu alloy
Contact surface material	gold-plated
Contact carrier material	PA
Material of contact, master cable side	CU alloy
Material of the contact carrier on the master cable side	PA
Material of contact surface, master cable side	Sn

Cable/line

Connection method	Pluggable screw connection
-------------------	----------------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 80 °C

Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

SACB-4/ 4-L-C GG SCO P - Distributor box header




1452864

<https://www.phoenixcontact.com/pc/products/1452864>

Drawings

Dimensional drawing



<https://www.phoenixcontact.com/pc/products/1452864>

The diagram illustrates a 5-phase motor drive system. It features 8 power semiconductors (IGBTs or MOSFETs) and 5 diodes. The power semiconductors are arranged in two rows of four, with a central break indicated by a wavy line. The diodes are connected in anti-parallel to the power semiconductors. The circuit is powered by a DC source U_N and a ground connection. The output terminals are labeled 0V, 1/4, 2/4, 6/4, 7/4, 8/4, and U_N . The motor windings are represented by circles with five terminals each, labeled 1, 3, 4, 5, and 1. The winding connections are shown as follows: for the first winding, terminal 1 is connected to the 0V line, 3 to the 1/4 line, 4 to the 2/4 line, 5 to the 6/4 line, and 1 to the 7/4 line; for the second winding, terminal 1 is connected to the 1/4 line, 3 to the 2/4 line, 4 to the 6/4 line, 5 to the 7/4 line, and 1 to the 8/4 line; for the third winding, terminal 1 is connected to the 2/4 line, 3 to the 6/4 line, 4 to the 7/4 line, 5 to the 8/4 line, and 1 to the U_N line; for the fourth winding, terminal 1 is connected to the 6/4 line, 3 to the 7/4 line, 4 to the 8/4 line, 5 to the U_N line, and 1 to the 0V line; for the fifth winding, terminal 1 is connected to the 7/4 line, 3 to the 8/4 line, 4 to the U_N line, 5 to the 0V line, and 1 to the 1/4 line.

Apr 1, 2024, 6:01 AM Page 5 (8)

SACB-4/ 4-L-C GG SCO P - Distributor box header



1452864

<https://www.phoenixcontact.com/pc/products/1452864>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1452864>

 cUL Recognized Approval ID: FILE E 118976				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	24 V	-	-	-

 UL Recognized Approval ID: FILE E 118976				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	24 V	-	-	-

cULus Recognized				
-------------------------	--	--	--	--

SACB-4/ 4-L-C GG SCO P - Distributor box header



1452864

<https://www.phoenixcontact.com/pc/products/1452864>

Classifications

ECLASS

ECLASS-11.0	27440111
ECLASS-12.0	27440111
ECLASS-13.0	27440111

ETIM

ETIM 9.0	EC003558
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SACB-4/ 4-L-C GG SCO P - Distributor box header



1452864

<https://www.phoenixcontact.com/pc/products/1452864>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com