

SACB-C-H180-6/ 6-10,0PUR SCO P - Connector hood



1453122

<https://www.phoenixcontact.com/pc/products/1453122>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector hood, application: Sensor/actuator box, connection method: M12-SPEEDCON-socket Plastic, number of slots: 6, slot assignment: single, status display: No; master cable connection: Pluggable screw connection 180°, PUR/PVC, cable length: 10 m, shielding: no

Commercial data

Item number	1453122
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF3CBG
Catalog page	Page 263 (C-2-2019)
GTIN	4046356553384
Weight per piece (including packing)	1,028.7 g
Weight per piece (excluding packing)	1,028.7 g
Customs tariff number	85444290
Country of origin	DE

1453122

<https://www.phoenixcontact.com/pc/products/1453122>

Technical data

Notes

General

NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.

Product properties

Product type	Connector hood
Application	Sensor/actuator box
Number of slots	6

Electrical properties

Nominal voltage U_N	120 V AC
	120 V DC
Rated current, total	10 A
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	4 A

Connection data

Conductor connection

Connection method	Pluggable screw connection
Tightening torque, cover screw	1 Nm

Pin assignment

Slot/position = Wire color or connection	1 / 4 (A) = WH
	2 / 4 (A) = GN
	3 / 4 (A) = YE
	4 / 4 (A) = GY
	5 / 4 (A) = PK
	6 / 4 (A) = RD
	1-6 / 1 (+ 120 V) = BN
	1-6 / 3 (0 V) = BU
	1-6 / 5 (PE) = GNYE

Signaling

Status display present	No
------------------------	----


Dimensions

SACB-C-H180-6/ 6-10,0PUR SCO P - Connector hood



1453122

<https://www.phoenixcontact.com/pc/products/1453122>

Dimensional drawing	
Width	54 mm
Height	25 mm
Length	34 mm


Material specifications

Material Housing	PBT
Seal material	NBR
Material of contact, master cable side	CU alloy
Material of the contact carrier on the master cable side	PA
Material of contact surface, master cable side	Sn

Cable/line

Cable length	10 m
--------------	------

PUR/PVC black [PUR]

Dimensional drawing	
Cable weight	96.6 kg/km
UL AWM Style	20549
Number of positions	9
Shielded	no
Cable type	PUR/PVC black [PUR]
Conductor structure signal line	19x 0.15 mm
AWG signal line	22
Conductor cross section	6x 0.34 mm ² (Signal line) 3x 0.75 mm ² (power line)
Wire diameter incl. insulation	1.3 mm ±0.1 mm (Signal line) 1.8 mm ±0.1 mm (power line)
External cable diameter	8.00 mm ±0.2 mm
Outer sheath, material	PUR

SACB-C-H180-6/ 6-10,0PUR SCO P - Connector hood



1453122

<https://www.phoenixcontact.com/pc/products/1453122>

External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, green/yellow, white, green, yellow, gray, pink, red
Thickness, insulation	≥ 0.15 mm (Inner sheath)
	≥ 0.38 mm (Outer cable sheath)
Overall twist	Wires twisted in layers
Nominal voltage, cable	300 V
Test voltage	2000 V
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	60 mm
Smallest bending radius, movable installation	80 mm
Max. bending cycles	1500000
Flame resistance	DIN EN 50265
Resistance to oil	according to VDE 0472 Part 803
Other resistance	Highly resistant to acids, alkaline solutions and solvents
Special properties	Silicone-free
Ambient temperature (operation)	-40 °C ... 90 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)
	80 °C (in acc. with UL)

Environmental and real-life conditions

Ambient conditions



Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 80 °C

1453122

<https://www.phoenixcontact.com/pc/products/1453122>

Drawings

Dimensional drawing



SACB-C-H180-6/ 6-10,0PUR SCO P - Connector hood




1453122


<https://www.phoenixcontact.com/pc/products/1453122>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1453122>



cUL Recognized
Approval ID: FILE E 118976



UL Recognized
Approval ID: FILE E 118976



EAC
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

SACB-C-H180-6/ 6-10,0PUR SCO P - Connector hood



1453122

<https://www.phoenixcontact.com/pc/products/1453122>

Classifications

ECLASS

ECLASS-11.0	27440108
ECLASS-12.0	27440108
ECLASS-13.0	27440108

ETIM

ETIM 9.0	EC002585
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com