

SACB-C-H180-8/ 8- 5,0PUR SCO P - Connector hood



1453177

<https://www.phoenixcontact.com/pc/products/1453177>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector hood, application: Sensor/actuator box, connection method: M12-SPEEDCON-socket Plastic, number of slots: 8, slot assignment: single, status display: No; master cable connection: Pluggable screw connection 180°, PUR/PVC, cable length: 5 m, shielding: no

Commercial data

Item number	1453177
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF3CBG
Catalog page	Page 263 (C-2-2019)
GTIN	4046356553414
Weight per piece (including packing)	638.4 g
Weight per piece (excluding packing)	613 g
Customs tariff number	85444290
Country of origin	DE

1453177

<https://www.phoenixcontact.com/pc/products/1453177>

Technical data

Notes

General

NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.

Product properties

Product type	Connector hood
Application	Sensor/actuator box
Number of slots	8

Electrical properties

Nominal voltage U_N	120 V AC
	120 V DC
Rated current, total	10 A
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	4 A

Connection data

Conductor connection

Connection method	Pluggable screw connection
Tightening torque, cover screw	1 Nm

Pin assignment

Slot/position = Wire color or connection	1 / 4 (A) = WH
	2 / 4 (A) = GN
	3 / 4 (A) = YE
	4 / 4 (A) = GY
	5 / 4 (A) = PK
	6 / 4 (A) = RD
	7 / 4 (A) = BK
	8 / 4 (A) = VT
	1-8 / 1 (+ 120 V) = BN
	1-8 / 3 (0 V) = BU
	1-8 / 5 (PE) = GNYE

Signaling

Status display present	No
------------------------	----


Dimensions

SACB-C-H180-8/ 8- 5,0PUR SCO P - Connector hood



1453177

<https://www.phoenixcontact.com/pc/products/1453177>

Dimensional drawing		
Width		54 mm
Height		25 mm
Length		34 mm


Material specifications

Material Housing	PBT
Seal material	NBR
Material of contact, master cable side	CU alloy
Material of the contact carrier on the master cable side	PA
Material of contact surface, master cable side	Sn

Cable/line

Cable length	5 m
--------------	-----

PUR/PVC black [PUR]

Dimensional drawing		
Cable weight		107.4 kg/km
UL AWM Style		20549 (80°C/300 V)
Number of positions		11
Shielded		no
Cable type		PUR/PVC black [PUR]
Conductor structure signal line		19x 0.15 mm
AWG signal line		22
Conductor cross section		8x 0.34 mm ² (Signal line)
		3x 0.75 mm ² (power line)
Wire diameter incl. insulation		1.3 mm ±0.1 mm (Signal line)
		1.8 mm ±0.1 mm (power line)
External cable diameter		8.50 mm ±0.2 mm
Outer sheath, material		PUR

SACB-C-H180-8/ 8- 5,0PUR SCO P - Connector hood



1453177

<https://www.phoenixcontact.com/pc/products/1453177>

External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, green/yellow, white, green, yellow, gray, pink, red, black, violet
Inner sheath thickness	≥ 0.15 mm
Thickness, outer sheath	≥ 0.38 mm
Overall twist	Wires twisted in layers
Max. conductor resistance	≤ 53 Ω/km (Signal line)
	≤ 26 Ω/km (power line)
Insulation resistance	≥ 5 MΩ*km
Nominal voltage, cable	300 V AC
Test voltage Core/Core	2000 V (50 Hz, 5 min.)
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	64 mm
Smallest bending radius, movable installation	85 mm
Max. bending cycles	1500000
Flame resistance	DIN EN 50265
Resistance to oil	according to VDE 0472 Part 803
Other resistance	Highly resistant to acids, alkaline solutions and solvents
Special properties	Silicone-free
Ambient temperature (operation)	-40 °C ... 90 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions



Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 80 °C

1453177

<https://www.phoenixcontact.com/pc/products/1453177>

Drawings

Dimensional drawing



SACB-C-H180-8/ 8- 5,0PUR SCO P - Connector hood




1453177


<https://www.phoenixcontact.com/pc/products/1453177>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1453177>



cUL Recognized
Approval ID: FILE E 118976



UL Recognized
Approval ID: FILE E 118976



EAC
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

SACB-C-H180-8/ 8- 5,0PUR SCO P - Connector hood



1453177

<https://www.phoenixcontact.com/pc/products/1453177>

Classifications

ECLASS

ECLASS-11.0	27440108
ECLASS-12.0	27440108
ECLASS-13.0	27440108

ETIM

ETIM 9.0	EC002585
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SACB-C-H180-8/ 8- 5,0PUR SCO P - Connector hood



1453177

<https://www.phoenixcontact.com/pc/products/1453177>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com