

SACC-DSI-MINFS-3CON-M26/1,0 - Device connector rear mounting



1453782

<https://www.phoenixcontact.com/ca/products/1453782>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator flush-type socket, 3-pos., 7/8", rear mounting with M26 fastening thread, with 1.0 m PE litz wire, 3 x 0.75 mm²

Commercial data

Item number	1453782
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AB25
Product key	ABQPAA
Catalog page	Page 50 (C-4-2015)
GTIN	4046356557832
Weight per piece (including packing)	110.94 g
Weight per piece (excluding packing)	110.94 g
Customs tariff number	85366940
Country of origin	DE

SACC-DSI-MINFS-3CON-M26/1,0 - Device connector rear mounting



1453782

<https://www.phoenixcontact.com/ca/products/1453782>

Technical data

Mounting

Mounting type	Rear mounting M26
---------------	-------------------

Product properties

Product type	Circular connectors (device side)
Number of positions	3
No. of cable outlets	1
Shielded	no

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PUR
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Contact resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	250 V
Nominal current I_N	12 A

Connection data

Conductor connection

Connection method	Individual wires
-------------------	------------------

Connector

Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	7/8"-16UNF

Cable/line

Cable length	1 m
Cable type	PVC litz wire
Wire diameter incl. insulation	2.7 mm

SACC-DSI-MINFS-3CON-M26/1,0 - Device connector rear mounting



1453782

<https://www.phoenixcontact.com/ca/products/1453782>

Single wire, color	green/yellow, brown, blue
Cable cross section	0.75 mm²
Conductor structure signal line	24x 0.20 mm
AWG signal line	18
Material wire insulation	PVC
Thickness, insulation	0.85 mm (Core insulation)
Ambient temperature (operation)	-40 °C ... 85 °C (cable, fixed installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
	IP67
Ambient temperature (operation)	-40 °C ... 85 °C (Socket)
	-40 °C ... 85 °C (cable, fixed installation)

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
8240 Parkhill Drive
Milton, Ontario L9T 5V7
1-800-890-2820
cdinfo@phoenixcontact.ca