

# SAC-4P-M12MS/ 5,0-28X OD - Sensor/actuator cable



1454053

<https://www.phoenixcontact.com/us/products/1454053>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 4-position, PE-X halogen-free, black-gray RAL 7021, Plug straight M12, coding: A, on free cable end, cable length: 5 m, for outdoor applications, with high-grade steel knurl

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Robust throughout: resistant to oil, UV, and ozone, withstands temperatures from -40°C ... +105°C

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1454053             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF03                |
| Product key                          | BF1CCA              |
| Catalog page                         | Page 153 (C-4-2013) |
| GTIN                                 | 4046356568661       |
| Weight per piece (including packing) | 228.6 g             |
| Weight per piece (excluding packing) | 231.5 g             |
| Customs tariff number                | 85444290            |
| Country of origin                    | PL                  |

# SAC-4P-M12MS/ 5,0-28X OD - Sensor/actuator cable



1454053

<https://www.phoenixcontact.com/us/products/1454053>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Application          | External areas        |
| Number of positions  | 4                     |
| No. of cable outlets | 1                     |
| Shielded             | no                    |
| Coding               | A                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|                                        |                 |
|----------------------------------------|-----------------|
| Flammability rating according to UL 94 | V0              |
| Seal material                          | FPM             |
| Material of grip body                  | PP              |
| Contact material                       | CuSn            |
| Contact surface material               | Ni/Au           |
| Contact carrier material               | PP              |
| Material for screw connection          | Stainless steel |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 250 V AC                   |
|                       | 250 V DC                   |
| Nominal current $I_N$ | 4 A                        |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | No |
| Status display present | No |

### Connection data

#### Conductor connection

|                   |                        |
|-------------------|------------------------|
| Tightening torque | 0.4 Nm (M12 connector) |
|-------------------|------------------------|

### Connector

#### Connection 1

# SAC-4P-M12MS/ 5,0-28X OD - Sensor/actuator cable



1454053

<https://www.phoenixcontact.com/us/products/1454053>

|                     |                   |
|---------------------|-------------------|
| Type                | Plug straight M12 |
| Number of positions | 4                 |
| Coding type         | A                 |


## Connection 2

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

## Cable/line

|              |     |
|--------------|-----|
| Cable length | 5 m |
|--------------|-----|

## PE-X black [28X]

|                                               |                                                                                     |
|-----------------------------------------------|-------------------------------------------------------------------------------------|
| Dimensional drawing                           |  |
| Cable weight                                  | 44 kg/km                                                                            |
| Number of positions                           | 4                                                                                   |
| Shielded                                      | no                                                                                  |
| Cable type                                    | PE-X black [28X]                                                                    |
| Conductor structure signal line               | 28x 0.15 mm                                                                         |
| AWG signal line                               | 20                                                                                  |
| Conductor cross section                       | 4x 0.5 mm <sup>2</sup> (Signal line)                                                |
| Wire diameter incl. insulation                | 1.6 mm ±0.05 mm (Signal line)                                                       |
| External cable diameter                       | 5.20 mm ±0.2 mm                                                                     |
| Outer sheath, material                        | PE-X                                                                                |
| External sheath, color                        | black-gray RAL 7021                                                                 |
| Conductor material                            | Bare Cu litz wires                                                                  |
| Material wire insulation                      | PE-X                                                                                |
| Single wire, color                            | brown, white, blue, black                                                           |
| Thickness, insulation                         | approx. 0.30 mm (Core insulation)<br>approx. 0.60 mm (Outer cable sheath)           |
| Overall twist                                 | 4 wires, twisted                                                                    |
| Length of twist, overall twist                | 61.6 mm                                                                             |
| Max. conductor resistance                     | ≤ 39 Ω/km (at 20 °C)                                                                |
| Insulation resistance                         | ≥ 100 MΩ*km (at 20 °C)                                                              |
| Nominal voltage, cable                        | ≤ 300 V AC                                                                          |
| Test voltage                                  | ≥ 3000 V AC                                                                         |
| Smallest bending radius, fixed installation   | 26 mm                                                                               |
| Smallest bending radius, movable installation | 52 mm                                                                               |
| Max. bending cycles                           | 2000000                                                                             |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815                                            |

# SAC-4P-M12MS/ 5,0-28X OD - Sensor/actuator cable



1454053

<https://www.phoenixcontact.com/us/products/1454053>

|                                 |                                                  |
|---------------------------------|--------------------------------------------------|
| Flame resistance                | according to DIN 60332-1-2                       |
|                                 | according to DIN EN 50266-2-5                    |
|                                 | according to IEC 60332-3-25 (bunched fire test)  |
| Fume corrosiveness              | according to IEC 60754                           |
| Concentration of fumes          | according to DIN EN 61034                        |
| Resistance to oil               | in accordance with DIN EN 60811-2-1              |
| Other resistance                | UV resistant (according to DIN VDE 0276-605)     |
| Special properties              | Irradiated                                       |
| Ambient temperature (operation) | -40 °C ... 105 °C (cable, fixed installation)    |
|                                 | -15 °C ... 105 °C (Cable, flexible installation) |
|                                 | 120 °C (at 48 h - see test report 19233)         |
|                                 | 180 °C (at 48 h - see test report 19233)         |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                                                                   |
|---------------------------------|-----------------------------------------------------------------------------------|
| Degree of protection            | IP65                                                                              |
|                                 | IP67                                                                              |
|                                 | IP68                                                                              |
|                                 | IP69K                                                                             |
| Ambient temperature (operation) | -40 °C ... 105 °C (Plug / socket)                                                 |
|                                 | -40 °C ... 85 °C (On sudden changes in temperature (according to IEC 60512-11-4)) |

## Standards and regulations

### M12

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)