

HC-B 06-TFL-H-O1M25S - Housing



1460019

<https://www.phoenixcontact.com/pc/products/1460019>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B6, for single locking latch, material: die-cast aluminum, cable outlets: 1, lateral, 1x M25, height: 72 mm, cable gland: none

Commercial data

Item number	1460019
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	BF7AAC
GTIN	4046356792325
Weight per piece (including packing)	170.27 g
Weight per piece (excluding packing)	168.64 g
Customs tariff number	85389099
Country of origin	DE

HC-B 06-TFL-H-O1M25S - Housing



1460019

<https://www.phoenixcontact.com/pc/products/1460019>

Technical data


Notes

General	For contact inserts HC-B6, BB10, DD24, M
---------	--

Product properties

Type	B6
Product type	Housing with locking latch
No. of cable outlets	1
Type of the screw connection	1x M25
Housing type	Sleeve housing
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	43 mm
Height	72 mm
Length	60 mm

Material specifications

Housing surface material	Powder-coated, gray
Housing material	die-cast aluminum

Mechanical properties

Mechanical data

Type of the screw connection	1x M25
------------------------------	--------

Mounting

Assembly instructions	For half and full screw connections
-----------------------	-------------------------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

HC-B 06-TFL-H-O1M25S - Housing

1460019

<https://www.phoenixcontact.com/pc/products/1460019>



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com