

https://www.phoenixcontact.com/nz/products/1460112

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON B16 sleeve housing, for single locking latch, height: 76 mm, with 1 x Pg29 screw connection, straight cable outlet

### Commercial data

| Item number                          | 1460112       |
|--------------------------------------|---------------|
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 10 pc         |
| Sales key                            | BF7AAC        |
| Product key                          | BF7AAC        |
| GTIN                                 | 4046356793544 |
| Weight per piece (including packing) | 292.29 g      |
| Weight per piece (excluding packing) | 252.1 g       |
| Country of origin                    | DE            |

PHENIX

1460112

https://www.phoenixcontact.com/nz/products/1460112



### Technical data

#### Notes


| General            | For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K |
|--------------------|---|
| Product properties |   |

## Product properties

| Туре                         | B16                        |
|------------------------------|----------------------------|
| Product type                 | Housing with locking latch |
| No. of cable outlets         | 1                          |
| Type of the screw connection | 1x Pg29                    |
| Housing type                 | Sleeve housing             |
| Cable outlet                 | straight                   |
| Pg screw connection          | with                       |

#### Dimensions

| Dimensional | drawing |
|-------------|---------|
|-------------|---------|



| Width                  | 43 mm |
|------------------------|-------|
| Height                 | 76 mm |
| Length                 | 94 mm |
| Wrench size, union nut | 37 mm |

### Material specifications

| Housing surface material | Powder-coated, gray |
|--------------------------|---------------------|
| Housing material         | die-cast aluminum   |

#### Mechanical properties

| Mechanical data              |             |
|------------------------------|-------------|
| Type of the screw connection | 1x Pg29     |
| Cable/line                   |             |
| External cable diameter ()   | 18 mm 27 mm |


#### Environmental and real-life conditions


| Ambient conditions              |               |
|---------------------------------|---------------|
| Degree of protection            | IP65          |
| Ambient temperature (operation) | -40 °C 125 °C |

1460112

https://www.phoenixcontact.com/nz/products/1460112

### Drawings





Dimensional drawing

### Dimensional drawing



1460112

https://www.phoenixcontact.com/nz/products/1460112



### Classifications

#### ECLASS

| ECLASS-11.0 | 27440202 |
|-------------|----------|
| ECLASS-13.0 | 27440202 |
|             |          |

### UNSPSC

1460112

https://www.phoenixcontact.com/nz/products/1460112



### Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Ltd Unit 15C, 906-930 Great South Road, Penrose Auckland 1061 0508 474 636 sales@phoenixcontact.co.nz