

HC-B 16-TMQ-H-M1PG29G - Housing



1460173

<https://www.phoenixcontact.com/us/products/1460173>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON B16 sleeve housing, with double locking latch, height: 72 mm, with 1 x Pg29 screw connection, straight cable outlet

Commercial data

Item number	1460173
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF55
Product key	BF7AAC
Catalog page	Page 518 (C-4-2013)
GTIN	4046356794022
Weight per piece (including packing)	320.6 g
Weight per piece (excluding packing)	309.8 g
Customs tariff number	85389099
Country of origin	DE

HC-B 16-TMQ-H-M1PG29G - Housing



1460173

<https://www.phoenixcontact.com/us/products/1460173>

Technical data


Notes

General	For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K
---------	---

Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Application	Standard
Type	B16
No. of cable outlets	1
Type of the screw connection	1x Pg29
Cable outlet	straight
Pg screw connection	with

Dimensions

Dimensional drawing	
Width	43 mm
Height	76 mm
Length	93.5 mm
Wrench size, union nut	37 mm

Material specifications

Material Screw connection	Brass, nickel-plated
Seal material Cable seal	NBR
Housing material	die-cast aluminum
Housing surface material	Powder-coated, gray
Locking latch material	Stainless steel, handle: PA

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg29
Locking type	Latch

Cable/line

External cable diameter Cable 1	18 mm ... 27 mm
---------------------------------	-----------------

Connection data

HC-B 16-TMQ-H-M1PG29G - Housing



1460173

<https://www.phoenixcontact.com/us/products/1460173>

External cable diameter	18 mm ... 27 mm
-------------------------	-----------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

HC-B 16-TMQ-H-M1PG29G - Housing


1460173

<https://www.phoenixcontact.com/us/products/1460173>



Drawings

Dimensional drawing



Dimensional drawing

HC-B 16-TMQ-H-M1PG29G - Housing



1460173

<https://www.phoenixcontact.com/us/products/1460173>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202

UNSPSC

UNSPSC 21.0	31261501
-------------	----------

HC-B 16-TMQ-H-M1PG29G - Housing



1460173

<https://www.phoenixcontact.com/us/products/1460173>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com