

1460298

https://www.phoenixcontact.com/us/products/1460298

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON B10 coupling housing, with double locking latch, height: 77.5 mm, with 1 x Pg21 gland, straight cable outlet

Commercial data

Item number	1460298
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF55
Product key	BF7AAC
Catalog page	Page 228 (NTK-2012)
GTIN	4046356695350
Weight per piece (including packing)	237.36 g
Weight per piece (excluding packing)	237.36 g
Customs tariff number	85389099
Country of origin	DE



https://www.phoenixcontact.com/us/products/1460298



Technical data

Notes

General	For contact inserts HC-B10, BB18, DD42, M, K8/24
---------	--

Product properties

Product type	Housing with locking latch
Housing type	Coupling housings
Application	Standard
Туре	B10
No. of cable outlets	1
Type of the screw connection	1x Pg21
Shielded	no
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	73 119 57
Width	43 mm
Height	77.5 mm
Length	73 mm

Material specifications

Seal material	NBR
Housing material	die-cast aluminum
Housing surface material	Powder-coated, gray
Locking latch material	Stainless steel, handle: PA

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg21
Locking type	Latch

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C 125 °C



https://www.phoenixcontact.com/us/products/1460298



Drawings

Dimensional drawing 73 119 Dimensional drawing

Dimensional drawing



1460298

https://www.phoenixcontact.com/us/products/1460298

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202



1460298

https://www.phoenixcontact.com/us/products/1460298

Environmental product compliance

EU R	oHS
------	-----

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/1460298



Accessories

G-INS-PG21-M68N-PNES-GY - Cable gland

1411145

https://www.phoenixcontact.com/us/products/1411145



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 13 mm ... 18 mm, shielding: no, connecting thread: Pg21, color: silver-grey RAL 7001

G-INS-PG21-M68N-NNES-S - Cable gland

1411175

https://www.phoenixcontact.com/us/products/1411175



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 13 mm ... 18 mm, shielding: no, connecting thread: Pg21, color: silver, with O-ring



https://www.phoenixcontact.com/us/products/1460298



G-INSEC-PG21-M68N-NNES-S - Cable gland

1411200

https://www.phoenixcontact.com/us/products/1411200



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 13 mm ... 18 mm, shielding: yes, connecting thread: Pg21, color: silver, with O-ring

HC-BS-PG21 - Screw plug

1674529

https://www.phoenixcontact.com/us/products/1674529



Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: Pg21, color: silver

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com