

https://www.phoenixcontact.com/us/products/1460314



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON B16 coupling housing, with double locking latch, height: 82 mm, with 1 x Pg29 gland, straight cable outlet

Commercial data

Item number	1460314
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF55
Product key	BF7AAC
Catalog page	Page 516 (C-4-2013)
GTIN	4046356695770
Weight per piece (including packing)	282.7 g
Weight per piece (excluding packing)	282.7 g
Customs tariff number	85389099
Country of origin	DE



https://www.phoenixcontact.com/us/products/1460314



Technical data

Notes

General	For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M,
	K

Product properties

Product type	Housing with locking latch
Housing type	Coupling housings
Application	Standard
Туре	B16
No. of cable outlets	1
Type of the screw connection	1x Pg29
Shielded	no
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	94 140
Width	43 mm
Height	82 mm
Length	94 mm

Material specifications

Seal material	NBR
Housing material	die-cast aluminum
Housing surface material	Powder-coated, gray
Locking latch material	Stainless steel, handle: PA

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg29
Locking type	Latch

Mounting

Assembly note	For half and full screw connections

Environmental and real-life conditions

Ambient conditions



1460314

https://www.phoenixcontact.com/us/products/1460314

Degree of protection	IP65
Ambient temperature (operation)	-40 °C 125 °C



https://www.phoenixcontact.com/us/products/1460314



Drawings

Dimensional drawing 8 94 140 57

Dimensional drawing



1460314

https://www.phoenixcontact.com/us/products/1460314

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202



1460314

https://www.phoenixcontact.com/us/products/1460314

Environmental product compliance

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/1460314



Accessories

G-INS-PG29-M68N-PNES-GY - Cable gland

1411146

https://www.phoenixcontact.com/us/products/1411146



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 18 mm ... 25 mm, shielding: no, connecting thread: Pg29, color: silver-grey RAL 7001

G-INS-PG29-M68N-NNES-S - Cable gland

1411176

https://www.phoenixcontact.com/us/products/1411176



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 18 mm ... 25 mm, shielding: no, connecting thread: Pg29, color: silver, with O-ring



https://www.phoenixcontact.com/us/products/1460314



G-INSEC-PG29-M68N-NNES-S - Cable gland

1411201

https://www.phoenixcontact.com/us/products/1411201



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 18 mm ... 25 mm, shielding: yes, connecting thread: Pg29, color: silver, with O-ring

HC-BS-PG29 - Screw plug

1674532

https://www.phoenixcontact.com/us/products/1674532



Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: Pg29, color: silver

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com