

1460330

https://www.phoenixcontact.com/us/products/1460330

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON B24 coupling housing, with double locking latch, height: 81.5 mm, with 1 x Pg29 gland, straight cable outlet

Commercial data

Item number	1460330
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF55
Product key	BF7AAC
Catalog page	Page 534 (C-4-2013)
GTIN	4046356696166
Weight per piece (including packing)	330.64 g
Weight per piece (excluding packing)	311 g
Customs tariff number	85389099
Country of origin	DE



https://www.phoenixcontact.com/us/products/1460330



Technical data

Notes

General For contact	inserts HC-B24, BB46, BBB64, D64, DD108, M
---------------------	--

Product properties

Product type	Housing with locking latch
Housing type	Coupling housings
Application	Standard
Туре	B24
No. of cable outlets	1
Type of the screw connection	1x Pg29
Shielded	no
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	120 - 130 - 57
Width	43 mm
Height	82 mm
Length	120 mm

Material specifications

Seal material	NBR
Housing material	die-cast aluminum
Housing surface material	Powder-coated, gray
Locking latch material	Stainless steel, handle: PA

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg29
Locking type	Latch

Mounting

Assembly note	For half and full screw connections
recomment necessity necess	To their differences of the control

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65



1460330

https://www.phoenixcontact.com/us/products/1460330

Ambient temperature (operation)	-40 °C 125 °C
---------------------------------	---------------





https://www.phoenixcontact.com/us/products/1460330



Drawings

Dimensional drawing





Dimensional drawing



1460330

https://www.phoenixcontact.com/us/products/1460330

Classifications

ECLASS

	ECLASS-11.0	27440202
	ECLASS-13.0	27440202
UN	ISPSC	



https://www.phoenixcontact.com/us/products/1460330



Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
FILDEAOU OVUO	
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/1460330



Accessories

G-INS-PG29-M68N-PNES-GY - Cable gland

1411146

https://www.phoenixcontact.com/us/products/1411146



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 18 mm ... 25 mm, shielding: no, connecting thread: Pg29, color: silver-grey RAL 7001

G-INS-PG29-M68N-NNES-S - Cable gland

1411176

https://www.phoenixcontact.com/us/products/1411176



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 18 mm ... 25 mm, shielding: no, connecting thread: Pg29, color: silver, with O-ring



https://www.phoenixcontact.com/us/products/1460330



G-INSEC-PG29-M68N-NNES-S - Cable gland

1411201

https://www.phoenixcontact.com/us/products/1411201



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 18 mm ... 25 mm, shielding: yes, connecting thread: Pg29, color: silver, with O-ring

HC-BS-PG29 - Screw plug

1674532

https://www.phoenixcontact.com/us/products/1674532



Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: Pg29, color: silver

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com