

Cable Catalog Number Explanation for μ 1200 and μ 1500 Base I/O to IFM Modules

Important: Use the following tables as a product configurator for pre-wired, and I/O module-ready cables for Bulletin **1764** MicroLogix 1500 and **1762** MicroLogix 1200 40 I/O controller digital I/O cables. All combinations of these fields make valid product catalog numbers. Refer to selection tables for IFM compatibility and ordering.

1492-CAB			010	A6x
Bulletin No.				
Digital Interface Cable				
Standard or Build-to-Order Length Cable				
005	0.5 m (1.64 ft)	Standard Length		
010	1.0 m (3.28 ft)			
025	2.5 m (8.20 ft)			
050	5.0 m (16.40 ft)			
001...	0.1...2.0 m (0.328...6.56 ft)	Build-to-Order Length		
020	0.1 m (0.328 ft) increments			
020...	2.0...10.0 m (6.56...32.8 ft)			
100	0.5 m (1.64 ft) increments			
100...	10.0...30.0 m (32.8...98.4 ft)			
300	1.0 m (3.28 ft) increments			

Cable Type for Bul. 1492-CAB010A62	
A62, B62	Pre-wired cables for Bulletin 1762 40 I/O controllers
X62	I/O-ready cable for 1762-L40AWA, -L40BxB, and -L40BWA inputs
T62	I/O-ready cable for 1762-L40AWA, -L40BxB and -L40BWA outputs

Cable Type for Bul. 1492-CAB010A64	
A64, B64, C64, F64	Pre-wired cables for Bulletin 1764 I/O base units
W64	I/O-ready cable for 1764-24AWA, -24BWA base unit inputs
X64	I/O-ready cable 1764-28BxB base unit inputs
T64	I/O-ready cable for 1764-24AWA, -24BWA base unit outputs
U64	I/O-ready cable for 1764-28BxB base unit outputs

Cable Catalog Number Explanation for 1794 Flex I/O to IFM Modules

Important: Use the following tables as a product configurator for pre-wired, and I/O module-ready cables for Bulletin **1794 Flex I/O, Cat. Nos. 1794-TB37DS, and 1794-TB62DS** base units. All combinations of these fields make valid product catalog number. Refer to selection tables for IFM compatibility and ordering.

1492-CAB			010	A94
Bulletin No.				
Digital Interface Cable				
Standard or Build-to-Order Length Cable				
005	0.5 m (1.64 ft)	Standard Length		
010	1.0 m (3.28 ft)			
025	2.5 m (8.20 ft)			
050	5.0 m (16.40 ft)			
001-020	0.1...2.0 m (0.328...6.56 ft) 0.1 m (0.328 ft) increments	Build-to-Order Length		
020-100	2.0...10.0 m (6.56...32.8 ft) 0.5 m (1.64 ft) increments			
100-300	10.0...30.0 m (32.8...98.4 ft) 1.0 m (3.28 ft) increments			

Cable Type	
A94	Pre-wired cables for Bulletin 1794 Flex digital I/O using the Bulletin 1794-TB37DS base
B94	Pre-wired cables for Bulletin 1794 Flex digital I/O using the Bulletin 1794-TB62DS base
G94	Digital I/O ready cable for digital I/O using the Bulletin 1794 TB37DS base
H94	Digital I/O ready cable for digital I/O using the Bulletin 1794 TB62DS base