




1492-WD3

1492-WD4

1492-WD6

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications

	Two-circuit terminal block.				Two-circuit terminal block.				Two-circuit terminal block.		
Approvals		EEx e II	CSA	IEC		EEx e II	CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC	420V	300V AC/DC	500V AC/DC	300V AC/DC	420V	300V AC/DC	500V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC
Maximum Current	15 A	24 A	15 A	24 A	20 A	24 A	20 A	32 A	50 A	55 A	41 A
Wire Range (Rated Cross Section)	#30... #14 AWG	2.5 mm ²	#22... #14 AWG	0.5... 2.5 mm ²	#22... #12 AWG	4 mm ²	#22... #12 AWG	0.5... 4 mm ²	#18... #8 AWG	#18... #8 AWG	0.5... 6 mm ²
Wire Strip Length	0.39" (10 mm)				0.39" (10 mm)				0.35" (9 mm)		
Recommended Tightening Torque	5.0...5.6 lb-in. (0.6 Nm)				5.0...5.6 lb-in. (0.6 Nm)				6.2 lb-in. (0.7 Nm)		
Density	60 pcs./ft (197/m)				50 pcs./ft (166/m)				43 pcs./ft (142/m)		
Insulation Temperature Range	-40...+195°F (-40...+90°C)				-40...+195°F (-40...+90°C)				-40...+195°F (-40...+90°C)		

Terminal Blocks

		Cat. No.	Pcs./Pkg.	Cat. No.	Pcs./Pkg.	Cat. No.	Pcs./Pkg.
Color:	Gray	1492-WD3	50	1492-WD4	50	1492-WD6	20
	Red	1492-WD3-RE	50	1492-WD4-RE	50	—	—
	Blue	1492-WD3-B	50	1492-WD4-B	50	—	—
	Black	1492-WD3-BL	50	1492-WD4-BL	50	—	—
	Green	1492-WD3-G	50	1492-WD4-G	50	—	—
	Yellow	1492-WD3-Y	50	1492-WD4-Y	50	—	—
	Orange	1492-WD3-OR	50	1492-WD4-OR	50	—	—
	Brown	1492-WD3-BR	50	1492-WD4-BR	50	—	—
	White	1492-WD3-W	50	1492-WD4-BR	50	—	—

Accessories (page 185)

	Cat. No.	Pcs./Pkg.	Cat. No.	Pcs./Pkg.	Cat. No.	Pcs./Pkg.
Mounting Rails:						
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10	199-DR1	10
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2	1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2	1492-DR7	2
End Barrier	1492-EBD3	50	1492-EBD3	50	1492-EBD6	50
End Anchor:						
DIN Rail - Normal Duty	1492-EA35	50	1492-EA35	50	1492-EA35	50
DIN Rail — Heavy Duty	1492-EAH35	10	1492-EAH35	10	1492-EAH35	10
Jumpers:			1492-N42 (2-pole)	50		
Insulated Side Jumper	1492-SJ5-10 (10-pole)	10	1492-SJ6-10 (10-pole)	10	—	—
Center Jumper — 50-pole	1492-CJD5-50	5	1492-CJD6-50	5	—	—
Center Jumper — 40-pole	—	—	—	—	1492-CJ7-40	5
Center Jumper — 10-pole	1492-CJD5-10	10	1492-CJD6-10	10	1492-CJ7-10	10
Center Jumper — 3-pole	1492-CJD5-3	10	1492-CJD6-3	10	1492-CJ7-3	10
Center Jumper — 2-pole	1492-CJD5-2	10	1492-CJD6-2	10	1492-CJ7-2	10
Center Jumper Link	1492-CJL5	10	1492-CJDL6	10	1492-CJL7	10
Other Accessories:						
Partition Plate	1492-PPD3	50	1492-PPD3	50	1492-PPD6	50
Separation Plate	1492-SPD3	50	1492-SPD3	50	—	—
Test Plug	—	—	1492-TP28	10	1492-TP28	10
Test Plug Adapter	1492-TA285	10	1492-TA40	10	1492-TA40	10
Electrical Warning Plate (4-pole)	1492-EWP5-4	10	1492-EWP6-4	10	1492-EWP7-4	10
Group Marking Carrier	1492-GM35	10	1492-GM35	10	1492-GM35	5
Marking Systems:						
Snap-in Marker Card	1492-SM5X9	5	1492-SM6X9	5	1492-SM6X12	5
Individual Marker Tabs (single char.)	1492-MP5 ❶	10	1492-MP ❶	10	1492-MP ❶	10

❶ Cat. no. is not complete. See page 186.