## 1492SPM3C200N

Allen-Bradley Miniature Circuit Breaker UL1077 10kA 3Pole plus Neutral 20A C Curve





| Component type | Miniature circuit breaker (MCB) |
|----------------|---------------------------------|
| Range          | Miniature Circuit Breaker       |
| Model          | N/A                             |
| Product status | New Item                        |

The Allen Bradley range of Miniature Circuit Breakers provide reliable and efficient protection for your electrical systems and their compact design assists with easy installation. Offering a broad portfolio of pole variants and current ratings, Allen Bradley circuit breakers can match the appropriate level of protection required for your application while contributing to operational efficiency.

|              | Rated current   | 20.0 A      |
|--------------|---|-------------|
| ELECTRICAL   | Number of poles (total)   | 4.0         |
|              | Release characteristic  | С           |
|              | Rated voltage   | 415.0 V     |
|              | Frequency   | 50 - 60 Hz  |
|              | Voltage type  | AC/DC       |
|              | Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V | 15.0 kA     |
|              | Rated impulse withstand voltage Uimp  | 4.0 kV      |
| CONSTRUCTION | Degree of protection (IP)   | IP40        |
| MECHANICAL   | Connectable conductor cross section solid-<br>core                          | 1 - 35 mm²  |
| DIMENSIONS   | Connectable conductor cross section multi-<br>wired                         | 1 - 25 mm²  |
|              | Height  | 80.0 mm     |
|              | Width   | 70.0 mm     |
|              | Depth   | 67.0 mm     |
|              | Weight  | 0.45 kg     |
| ENVIRONMENT  | Pollution degree  | 3.0         |
|              | Rated surrounding temperature without derating                              | 30.0 °C     |
|              | Ambient temperature during operating  | -25 - 55 °C |

Page 1 of 1 ©2022. NHP. All rights reserved