

1492W10

Allen-Bradley 1492-W Screw Connection Terminal 10mm 1
Level 2 Conductor Entries Grey



| | |
|----------------|-----------------------------|
| Component type | Feed-through terminal block |
| Range | 1492J/W |
| Model | N/A |
| Product status | Existing |

The Allen-Bradley 1492-J and W ranges of screw connection terminal blocks are reliable, safe and straightforward electrical connections designed for advanced wiring management. With cross-sectional wire sizes ranging from 0.5mm² to 120mm², and fitted with various terminal types such as feed-through, disconnect, fused and plug-in and available in both single and multi-level housing make them ideal for any panel space requirements. Available with a wide range of accessories enabling quick and easy installation.

| | | |
|--------------|--|-------------------------------|
| ELECTRICAL | Type of electrical connection 1 | Screw connection |
| | Rated current In | 57 A |
| | Rated voltage | 800 V |
| CONSTRUCTION | Number of levels | 1 |
| | Number of clamp positions per level | 2 |
| | Colour | Grey |
| | Mounting method | DIN rail (top hat rail) 35 mm |
| | Inflammability class of insulation material according to with UL94 | V0 |
| MECHANICAL | Nominal tightening torque | 1.4 Nm |
| DIMENSIONS | Wire/conductor size | 0.5-10 mm |
| | Width | 8 mm |
| | Height | 47.6 mm |
| | Depth | 41 mm |
| | Wire strip length | 13 mm |
| ENVIRONMENT | Insulation temperature | -40...90 °C |