

1492WM4B

Allen-Bradley 1492-W Screw Connection Mini Terminal 4mm 1
Level 2 Conductor Entries Blue



| | |
|----------------|-----------------------------|
| Component type | Feed-through terminal block |
| Range | 1492J/W |
| Model | N/A |
| Product status | Existing |

The Allen-Bradley 1492-J and W ranges of screw connection terminal blocks are reliable, safe and straight forward electrical connections for wiring management. With cross-sectional wire sizes from 0.5mm² to 120mm² and terminal types such as feed-through, disconnect, fused, plug-in and thermocouple. Options include single or multi-level housing and accessories for various panel space requirements.

| | | |
|--------------|--|-------------------------------|
| ELECTRICAL | Type of electrical connection 1 | Screw connection |
| | Rated current In | 32 A |
| | Rated voltage | 500 V |
| CONSTRUCTION | Number of levels | 1 |
| | Number of clamp positions per level | 2 |
| | Colour | Blue |
| | Mounting method | DIN rail (top hat rail) 35 mm |
| | Inflammability class of insulation material according to with UL94 | V0 |
| DIMENSIONS | Wire/conductor size | 0.5-4 mm |
| | Width | 6 mm |
| | Height | 32 mm |
| | Depth | 28 mm |
| | Wire strip length | 10 mm |
| ENVIRONMENT | Insulation temperature | -40...90 °C |
| | Operating temperature | ...40...90 °C |