

Specifications

Eaton 014979

Eaton Moeller® series T0 On-Off switch, T0, 20 A, service distribution board mounting, 5 contact unit(s), 10-pole, with black thumb grip and front plate

General specifications

PRODUCT NAME	Eaton Moeller® series T0 On-off switch
CATALOG NUMBER	014979
EAN	4015080149798
PRODUCT LENGTH/DEPTH	120 mm
PRODUCT HEIGHT	55 mm
PRODUCT WIDTH	54 mm
PRODUCT WEIGHT	0.205 kg
CERTIFICATIONS	CE CSA UL Category Control No.: NLRV CSA-C22.2 No. 94 CSA File No.: 012528 UL 60947-4-1 CSA-C22.2 No. 60947-4-1-14 VDE 0660 IEC/EN 60947-3 CSA Class No.: 3211-05 IEC/EN 60204 UL File No.: E36332 IEC/EN 60947 UL
CATALOG NOTES	Rated Short-time Withstand Current (I _{cw}) for a time of 1 second
MODEL CODE	T0-5-8346/IVS



Powering Business Worldwide

Features & Functions

FITTED WITH: Black thumb grip and front plate

INSCRIPTION 0-1

NUMBER OF POLES 10

General

DEGREE OF PROTECTION NEMA Other

DEGREE OF PROTECTION (FRONT SIDE) IP30

LIFESPAN, MECHANICAL 400,000 Operations

MOUNTING METHOD Service distribution board mounting

MOUNTING POSITION As required

NUMBER OF CONTACT UNITS 5

OPERATING FREQUENCY 1200 Operations/h

OVERVOLTAGE CATEGORY III

POLLUTION DEGREE 3

PRODUCT CATEGORY On-Off switch

RATED IMPULSE WITHSTAND VOLTAGE (UIMP) 6000 V AC

SAFE ISOLATION 440 V AC, Between the contacts, According to EN 61140

SAFETY PARAMETER (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1

SHOCK RESISTANCE 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms

SUITABLE FOR Distribution board installation
Ground mounting
Branch circuits, suitable as motor disconnect, (UL/CSA)

SWITCHING ANGLE 90 °

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Terminal capacities

TERMINAL CAPACITY	2 x (1 - 2.5) mm ² , solid or stranded 2 x (0.75 - 2.5) mm ² , flexible with ferrules to DIN 46228 18 - 14 AWG, solid or flexible with ferrule 1 x (0.75 - 2.5) mm ² , flexible with ferrules to DIN 46228 1 x (1 - 2.5) mm ² , solid or stranded
SCREW SIZE	M3.5, Terminal screw
TIGHTENING TORQUE	1 Nm, Screw terminals 8.8 lb-in, Screw terminals

Electrical rating

RATED BREAKING CAPACITY AT 220/230 V (COS PHI TO IEC 60947-3) 100 A

RATED BREAKING CAPACITY AT 400/415 V (COS PHI TO IEC 60947-3) 110 A

RATED BREAKING CAPACITY AT 500 V (COS PHI TO IEC 60947-3) 80 A

RATED BREAKING CAPACITY AT 660/690 V (COS PHI TO IEC 60947-3) 60 A

RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V 11.5 A

RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V 11.5 A

RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V 9 A

RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V 4.9 A

RATED OPERATIONAL CURRENT (IE) AT AC-21, 440 V 20 A

RATED OPERATIONAL CURRENT (IE) AT AC-23A, 230 V 13.3 A

RATED OPERATIONAL CURRENT (IE) AT AC-23A, 400 V, 415 V 13.3 A

RATED OPERATIONAL CURRENT (IE) AT AC-23A, 500 V 13.3 A

RATED OPERATIONAL CURRENT (IE) AT AC-23A, 690 V 7.6 A

RATED OPERATIONAL CURRENT (IE) AT DC-1, LOAD-BREAK SWITCHES L/R = 1 MS 10 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, CONTROL SWITCHES L/R = 50 MS 10 A

RATED OPERATIONAL CURRENT (IE) AT DC-21, 1 A

Short-circuit rating

RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ) 6 kA

RATED SHORT-TIME WITHSTAND CURRENT (ICW) 320 A, Contacts, 1 second
0.32 kA

SHORT-CIRCUIT CURRENT RATING (BASIC RATING) 50A, max. Fuse, SCCR (UL/CSA)
5 kA, SCCR (UL/CSA)

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT) 10 kA, SCCR (UL/CSA)
20 A, Class J, max. Fuse, SCCR (UL/CSA)

SHORT-CIRCUIT PROTECTION RATING 20 A gG/gL, Fuse, Contacts

240 V	
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 24 V	10 A
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 48 V	10 A
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 60 V	10 A
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 120 V	5 A
RATED OPERATIONAL CURRENT (IE) AT DC-23A, 240 V	5 A
RATED OPERATIONAL CURRENT (IE) STAR-DELTA AT AC-3, 220/230 V	20 A
RATED OPERATIONAL CURRENT (IE) STAR-DELTA AT AC-3, 380/400 V	20 A
RATED OPERATIONAL CURRENT (IE) STAR-DELTA AT AC-3, 500 V	15.6 A
RATED OPERATIONAL CURRENT (IE) STAR-DELTA AT AC-3, 690 V	8.5 A
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	5.5 kW
RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ	5.5 kW
RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	4 kW
RATED OPERATIONAL POWER AT AC-23A, 220/230 V, 50 HZ	3 kW
RATED OPERATIONAL POWER AT AC-23A, 400 V, 50 HZ	5.5 kW
RATED OPERATIONAL POWER AT AC-23A, 500 V, 50 HZ	7.5 kW
RATED OPERATIONAL POWER AT AC-23A, 690 V, 50 HZ	5.5 kW
RATED OPERATIONAL	5.5 kW

**POWER STAR-DELTA AT
220/230 V, 50 HZ**

RATED OPERATIONAL POWER STAR-DELTA AT 380/400 V, 50 HZ	7.5 kW
---	--------

RATED OPERATIONAL POWER STAR-DELTA AT 500 V, 50 HZ	7.5 kW
---	--------

RATED OPERATIONAL POWER STAR-DELTA AT 690 V, 50 HZ	5.5 kW
---	--------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
---	-------

RATED UNINTERRUPTED CURRENT (IU)	20 A
---	------

UNINTERRUPTED CURRENT	Rated uninterrupted current I _u is specified for max. cross-section.
----------------------------------	---

Switching capacity

	2 x I _e (with intermittent operation class 12, 25 % duty factor)
LOAD RATING	1.3 x I _e (with intermittent operation class 12, 60 % duty factor)
	1.6 x I _e (with intermittent operation class 12, 40 % duty factor)

NUMBER OF CONTACTS IN SERIES AT DC-21A, 240 V	1
--	---

NUMBER OF CONTACTS IN SERIES AT DC-23A, 24 V	1
---	---

NUMBER OF CONTACTS IN SERIES AT DC-23A, 48 V	2
---	---

NUMBER OF CONTACTS IN SERIES AT DC-23A, 60 V	3
---	---

NUMBER OF CONTACTS IN SERIES AT DC-23A, 120 V	3
--	---

NUMBER OF CONTACTS IN SERIES AT DC-23A, 240 V	5
--	---

SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)	16 A, Rated uninterrupted current max. (UL/CSA)
--	---

SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	10A, IU, (UL/CSA)
---	-------------------

SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600 (UL/CSA) P300 (UL/CSA)
--	--------------------------------

RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)	130 A
--	-------

VOLTAGE PER CONTACT PAIR IN SERIES	60 V
---	------

Motor rating

ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE	0.5 HP
--	--------

ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 1-PHASE	1 HP
--	------

ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE	3 HP
--	------

ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE	1.5 HP
--	--------

ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE	3 HP
--	------

ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	7.5 HP
--	--------

ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE	7.5 HP
--	--------

Contacts

CONTROL CIRCUIT RELIABILITY	1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
------------------------------------	---

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
--	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
--	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
--	---

Actuator

ACTUATOR COLOR	Black
-----------------------	-------

ACTUATOR FUNCTION	Maintained
--------------------------	------------

ACTUATOR TYPE	Short thumb-grip
----------------------	------------------

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.6 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	20 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

BROCHURES

[Brochure - T Rotary Cam switch and P Switch-disconnector](#)

CATALOGUES

[P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

DECLARATIONS OF CONFORMITY

[DA-DC-00004927.pdf](#) [DA-DC-00004895.pdf](#)

DRAWINGS

[eaton-rotary-switches-mounting-t0-step-switch-dimensions-006.eps](#)

	eaton-general-rotary-switch-t0-step-switch-symbol-005.eps
	eaton-rotary-switches-front-plate-t0-on-off-switch-symbol-002.eps
ECAD MODEL	eaton-t0-on-off-switch-eplan-014979.edz
INSTALLATION INSTRUCTIONS	IL03801006Z
INSTALLATION VIDEOS	Eaton's P Switch-disconnectors used in a factory
MCAD MODEL	DA-CS-t0_5_ivs DA-CD-t0_5_ivs
PRODUCT NOTIFICATIONS	MZ008005ZU_Orderform_Customized_Switch.pdf MZ008006ZU_Orderform_Customized_Switch.pdf
WIRING DIAGRAMS	eaton-rotary-switches-t0-on-off-switch-wiring-diagram-044.eps eaton-rotary-switches-t0-on-off-switch-wiring-diagram-043.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

