



Figure similar

Non-reversing motor starter Size 1 Three phase full voltage Solid-state overload relay OLRelay amp range 0.25-1A 110-120/220-240VAC 60HZ coil Combination type Water/dust tight non-corrosive

product brand name  
design of the product  
special product feature

Class 14  
Full-voltage non-reversing motor starter  
ESP200 overload relay; Dual voltage coil

### General technical data

weight [lb] 15 lb  
Height x Width x Depth [in] 13 × 13 × 5 in  
touch protection against electrical shock (NA for enclosed products)  
installation altitude [ft] at height above sea level maximum 6560 ft  
ambient temperature [°F]  
• during storage -22 ... +149 °F  
• during operation -4 ... +104 °F  
ambient temperature  
• during storage -30 ... +65 °C  
• during operation -20 ... +40 °C  
country of origin USA

### Horsepower ratings

yielded mechanical performance [hp] for 3-phase AC motor  
• at 200/208 V rated value 0.17 hp  
• at 220/230 V rated value 0.17 hp  
• at 460/480 V rated value 0.33 hp  
• at 575/600 V rated value 0.5 hp

### Contactors

size of contactor NEMA controller size 1  
number of NO contacts for main contacts 3  
operating voltage for main current circuit at AC at 60 Hz maximum 600 V  
operational current at AC at 600 V rated value 27 A  
mechanical service life (operating cycles) of the main contacts typical 10000000

### Auxiliary contact

number of NC contacts at contactor for auxiliary contacts 0  
number of NO contacts at contactor for auxiliary contacts 1  
number of total auxiliary contacts maximum 8  
contact rating of auxiliary contacts of contactor according to UL 10A@600VAC (A600), 5A@600VDC (P600)

### Coil

type of voltage of the control supply voltage AC  
control supply voltage  
• at AC at 60 Hz rated value 110 ... 240 V  
holding power at AC minimum 8.6 W

|                                                                          |              |
|--------------------------------------------------------------------------|--------------|
| apparent pick-up power of magnet coil at AC                              | 218 VA       |
| apparent holding power of magnet coil at AC                              | 25 VA        |
| operating range factor control supply voltage rated value of magnet coil | 0.85 ... 1.1 |
| percental drop-out voltage of magnet coil related to the input voltage   | 50 %         |
| ON-delay time                                                            | 19 ... 29 ms |
| OFF-delay time                                                           | 10 ... 24 ms |

#### Overload relay

|                                                                                     |                                      |
|-------------------------------------------------------------------------------------|--------------------------------------|
| product function                                                                    | Yes                                  |
| • overload protection                                                               | Yes                                  |
| • phase failure detection                                                           | Yes                                  |
| • asymmetry detection                                                               | Yes                                  |
| • ground fault detection                                                            | Yes                                  |
| • test function                                                                     | Yes                                  |
| • external reset                                                                    | Yes                                  |
| reset function                                                                      | Manual, automatic and remote         |
| trip class                                                                          | CLASS 5 / 10 / 20 (factory set) / 30 |
| adjustable current response value current of the current-dependent overload release | 0.25 ... 1 A                         |
| tripping time at phase-loss maximum                                                 | 3 s                                  |
| relative repeat accuracy                                                            | 1 %                                  |
| product feature protective coating on printed-circuit board                         | Yes                                  |
| number of NC contacts of auxiliary contacts of overload relay                       | 1                                    |
| number of NO contacts of auxiliary contacts of overload relay                       | 1                                    |
| operational current of auxiliary contacts of overload relay                         |                                      |
| • at AC at 600 V                                                                    | 5 A                                  |
| • at DC at 250 V                                                                    | 1 A                                  |
| contact rating of auxiliary contacts of overload relay according to UL              | 5A@600VAC (B600), 1A@250VDC (R300)   |
| insulation voltage (Ui)                                                             |                                      |
| • with single-phase operation at AC rated value                                     | 600 V                                |
| • with multi-phase operation at AC rated value                                      | 300 V                                |

#### Enclosure

|                                  |                                              |
|----------------------------------|----------------------------------------------|
| degree of protection NEMA rating | 4X, 304 stainless steel                      |
| design of the housing            | Extra-wide                                   |
| design of the housing            | Dust-tight, watertight & corrosion resistant |

#### Mounting/wiring

|                                                                                                                   |                                   |
|-------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| mounting position                                                                                                 | Vertical                          |
| fastening method                                                                                                  | Surface mounting and installation |
| type of electrical connection for supply voltage line-side                                                        | Screw-type terminals              |
| tightening torque [lbf-in] for supply                                                                             | 35 ... 35 lbf-in                  |
| type of connectable conductor cross-sections at line-side at AWG cables single or multi-stranded                  | 1x(14 - 2 AWG)                    |
| temperature of the conductor for supply maximum permissible                                                       | 75 °C                             |
| material of the conductor for supply                                                                              | AL or CU                          |
| type of electrical connection for load-side outgoing feeder                                                       | Screw-type terminals              |
| tightening torque [lbf-in] for load-side outgoing feeder                                                          | 20 ... 24 lbf-in                  |
| type of connectable conductor cross-sections at AWG cables for load-side outgoing feeder single or multi-stranded | 2 x (14 - 10 AWG)                 |
| temperature of the conductor for load-side outgoing feeder maximum permissible                                    | 75 °C                             |
| material of the conductor for load-side outgoing feeder                                                           | CU                                |
| type of electrical connection of magnet coil                                                                      | screw-type terminals              |
| tightening torque [lbf-in] at magnet coil                                                                         | 5 ... 12 lbf-in                   |
| type of connectable conductor cross-sections of magnet coil at AWG cables single or multi-stranded                | 2 x (16 - 12 AWG)                 |
| temperature of the conductor at magnet coil maximum permissible                                                   | 75 °C                             |
| material of the conductor at magnet coil                                                                          | CU                                |
| type of electrical connection for auxiliary contacts                                                              | screw-type terminals              |
| tightening torque [lbf-in] at contactor for auxiliary contacts                                                    | 10 ... 15 lbf-in                  |

|                                                                                                                              |                                                    |
|------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| type of connectable conductor cross-sections at contactor at AWG cables for auxiliary contacts single or multi-stranded      | 1 x (12 AWG), 2 x (16 - 14 AWG), 2 x (18 - 16 AWG) |
| temperature of the conductor at contactor for auxiliary contacts maximum permissible                                         | 75 °C                                              |
| material of the conductor at contactor for auxiliary contacts                                                                | CU                                                 |
| type of electrical connection at overload relay for auxiliary contacts                                                       | screw-type terminals                               |
| tightening torque [lbf·in] at overload relay for auxiliary contacts                                                          | 7 ... 10 lbf·in                                    |
| type of connectable conductor cross-sections at overload relay at AWG cables for auxiliary contacts single or multi-stranded | 2 x (20 - 14 AWG)                                  |
| temperature of the conductor at overload relay for auxiliary contacts maximum permissible                                    | 75 °C                                              |
| material of the conductor at overload relay for auxiliary contacts                                                           | CU                                                 |

#### Short-circuit current rating

|                                                                                   |                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------|
| design of the fuse link for short-circuit protection of the main circuit required | 10kA@600V (Class H or K); 100kA@600V (Class R or J) |
| design of the short-circuit trip                                                  | Thermal magnetic circuit breaker                    |
| maximum short-circuit current breaking capacity (I <sub>cu</sub> )                |                                                     |
| • at 240 V                                                                        | 14 kA                                               |
| • at 480 V                                                                        | 10 kA                                               |
| • at 600 V                                                                        | 10 kA                                               |
| certificate of suitability                                                        | NEMA ICS 2; UL 508; CSA 22.2, No.14                 |

#### Further information

##### Industrial Controls - Product Overview (Catalogs, Brochures,...)

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:14DUA82WA>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/US/en/ps/US2:14DUA82WA>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:14DUA82WA&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:14DUA82WA&lang=en)

##### Certificates/approvals

<https://support.industry.siemens.com/cs/US/en/ps/US2:14DUA82WA/certificate>



