

SACC-M16FR-14CON-M - Connector

1500253

<https://www.phoenixcontact.com/us/products/1500253>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

M16 socket, 14-pos., with solder connection, freely configurable, angled, for a 6.0 mm conductor diameter ... 8.0 mm



Commercial data

Item number	1500253
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF45
Product key	BF3ZDX
Catalog page	Page 311 (C-2-2019)
GTIN	4017918587918
Weight per piece (including packing)	68.9 g
Weight per piece (excluding packing)	68.9 g
Customs tariff number	85366990
Country of origin	DE

SACC-M16FR-14CON-M - Connector



1500253

<https://www.phoenixcontact.com/us/products/1500253>

Technical data

Notes

General	NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.
---------	--

Mounting

Connection method	Solder connection
-------------------	-------------------

Product properties

Product type	Circular connectors (device side)
Number of positions	14
Shielded	no
Coding	no

Dimensions

Width	20 mm
Height	37.4 mm
Length	54 mm

Material specifications

Material Threaded sleeve	Die-cast zinc
Flammability rating according to UL 94	V0
Contact material	CuSn
Contact surface material	Au
Contact carrier material	PBT

Electrical properties

Nominal voltage U_N	60 V DC (Overvoltage category I / degree of pollution 1)
	32 V AC (Overvoltage category II / degree of pollution 2)

Connection data

Conductor connection	
Connection method	Solder connection
Contact connection type	Socket

Connector

Connection 1	
Head design	Socket
Head cable outlet	angled
Head thread type	M16

SACC-M16FR-14CON-M - Connector



1500253

<https://www.phoenixcontact.com/us/products/1500253>

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-30 °C ... 95 °C

SACC-M16FR-14CON-M - Connector



1500253

<https://www.phoenixcontact.com/us/products/1500253>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-M16FR-14CON-M - Connector



1500253

<https://www.phoenixcontact.com/us/products/1500253>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com