

Specifications



Eaton 150643

Eaton Moeller® series M22 Accessory Contact element, 1 N/C, Front fastening, Front fixing, Single contact

General specifications



PRODUCT NAME	Eaton Moeller® series M22 Accessory Contact element
CATALOG NUMBER	150643
MODEL CODE	M22-K01PV6
EAN	4015081469550
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	32 mm
PRODUCT WIDTH	10 mm
PRODUCT WEIGHT	0.01 kg
CERTIFICATIONS	IEC 60947-5-1
CATALOG NOTES	Contacts with safety function, by positive opening to IEC/EN 60947-5-1
GLOBAL CATALOG	150643

Product specifications

10.10 TEMPERATURE RISE

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 MECHANICAL FUNCTION

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 CORROSION RESISTANCE

Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES

Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT

Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS

Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION

Meets the product standard's requirements.

10.2.5 LIFTING

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS

Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

Resources

CATALOGS

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

CERTIFICATION REPORTS

[000Z425](#)

CONTROL TRAVEL DIAGRAM

[eaton-operating-diagram-m22-contact-element-contact-travel-diagram-008.eps](#)

DECLARATIONS OF CONFORMITY

[eaton-accessory-declaration-of-conformity-eu250868en.pdf](#)

[DA-DC-00004134.pdf](#)

[DA-DC-00004971.pdf](#)

[DA-DC-00004176.pdf](#)

[DA-DC-00004157.pdf](#)

[DA-DC-00004135.pdf](#)

[DA-DC-00004975.pdf](#)

DRAWINGS

[eaton-circuit-breaker-release-nzm-mccb-dimensions.eps](#)

[eaton-operating-actuation-m22-led-element-dimensions.eps](#)

[eaton-general-standards-000Z425.jpg](#)

[eaton-operating-contact-m22-contact-element-3d-drawing-004.eps](#)

[eaton-operating-devices-adapter-flow-diagram-003.eps](#)

ECAD MODEL

[ETN.150643.edz](#)

FLYERS

[eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf](#)

INSTALLATION INSTRUCTIONS

[IL04716002Z](#)

[eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf](#)

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
ELECTRIC CONNECTION TYPE	Screw connection
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
ACTUATING FORCE - MAX	4 N
ACTUATOR TRAVEL AND ACTUATION FORCE (DIN EN 60947-5-1)	4.8 mm
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT STORAGE TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
FORCE FOR POSITIVE OPENING - MIN	15 N
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER	0.11 W

INSTALLATION VIDEOS	IL04716005Z.pdf
MCAD MODEL	DA-CD-kontaktelement schraube front DA-CS-kontaktelement schraube front
MULTIMEDIA	easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator MCI Multicolor Light Indicator M22 with SmartWire-DT RMQ small E-Stop emergency-stop button MCI MultiColor Light Indicator RMQ compact solution
SALES NOTES	eaton-control-circuit-devices_rmq-titan-f144090en-en-us.pdf eaton-rmq-small-e-stop-flyer-f1047006en-en-us.pdf eaton-rmq-flat-enclosure-flyer-f1047003en-en-us.pdf eaton-rmq-mci-multi-color-light-indicator-flyer-f1047005en-en-us.pdf
WIRING DIAGRAMS	eaton-operating-contact-m22-contact-element-wiring-diagram-003.eps eaton-circuit-breaker-contact-m22-contact-element-wiring-diagram.eps

POLE, CURRENT-DEPENDENT PVID	
KNOB TRAVEL	5.7 mm
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF SWITCHES (FAULT SIGNAL)	0
CONNECTION TO SMARTWIRE-DT	No
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	
CONNECTION TYPE	Single contact Front fixing
MOUNTING METHOD	Front fastening
OVERVOLTAGE CATEGORY	III
CONTROL CIRCUIT RELIABILITY	1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)
DEGREE OF PROTECTION	IP20
MODEL	Top mounting
LAMP HOLDER	None
RATED OPERATIONAL CURRENT (IE)	5 A - 600 V AC 1 A - 250 V DC
LIFESPAN, ELECTRICAL	1,200,000 Operations (at 12 V, DC-13, 2.8 A) 1,000,000 Operations (at 230 V, AC-15, 1 A) 700,000 Operations (at 230 V, AC-15, 3 A) 1,600,000 Operations (at 230 V, 0.5 A)
TERMINAL CAPACITY	0.5 - 2.5 mm ²

(STRANDED)

SHORT-CIRCUIT PROTECTION PKZM0-10/FAZ-B6/1,
Contacts, Max. short-circuit protective device,
Fuseless

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS 0 W

RATED OPERATIONAL CURRENT (IE) AT DC-13, 500 V 0.1 A

SHORT-CIRCUIT PROTECTION RATING Max. 10 A gG/gL, Fuse,
Contacts

OPERATING TORQUE 0.8 Nm

RATED INSULATION VOLTAGE (UI) 500 V

RATED OPERATIONAL CURRENT (IE) AT AC-15, 115 V 6 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V 6 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V 4 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V 2 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V 0.6 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V 0.3 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V 3 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 42 V 1.7 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V 1.2 A

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 6 A

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE) 0.5 - 1.5 mm²

TERMINAL CAPACITY (SOLID)	0.75 - 2.5 mm ²
SHOCK RESISTANCE	30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

