

SAC-2P-M12MSB/10,0-910/M12FSB - Bus system cable

1507395
<https://www.phoenixcontact.com/us/products/1507395>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bus system cable, PROFIBUS (12 Mbps), 2-position, PUR halogen-free, red lilac RAL 4001, shielded, Plug straight M12, coding: B, on Socket straight M12, coding: B, cable length: 10 m

Commercial data

Item number	1507395
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF04
Product key	BF1CKC
Catalog page	Page 429 (C-2-2019)
GTIN	4017918900212
Weight per piece (including packing)	610 g
Weight per piece (excluding packing)	610 g
Customs tariff number	85444290
Country of origin	PL

SAC-2P-M12MSB/10,0-910/M12FSB - Bus system cable



1507395

<https://www.phoenixcontact.com/us/products/1507395>

Technical data

Notes

General	Further products with variable cable lengths can be found in the accessories section
---------	--

Product properties

Product type	Data cable preassembled
Application	Standard
Sensor type	PROFIBUS
Number of positions	2
No. of cable outlets	1
Shielded	yes
Coding	B

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Interfaces

Bus system	PROFIBUS
Signal type/category	PROFIBUS, 12 Mbps (max. 100 m)

Signaling

Status display	No
Status display present	No

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A
Transmission medium	Copper

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Material specifications

Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA 6.6 (plug), TPU GF (socket)

SAC-2P-M12MSB/10,0-910/M12FSB - Bus system cable



1507395

<https://www.phoenixcontact.com/us/products/1507395>

Material for screw connection

Zinc die-cast, nickel-plated

Connection data

Pin assignment

Contact Color (signal designation) Contact (optional)

2 (Plug) GN (A cable) 2 (Socket)

4 (Plug) RD (B cable) 4 (Socket)

Connector

Connection 1

Type

Plug straight M12

Number of positions

2

Coding type

B (inverse)

Connection 2

Type

Socket straight M12

Number of positions

2

Coding type

B


Cable/line

Cable length

10 m

PROFIBUS [910]

Dimensional drawing



Cable weight

90 kg/km

UL AWM Style

21198 (80°C/300 V)

Number of positions

2

Shielded

yes

Cable type

PROFIBUS [910]

Conductor structure

1x2xAWG24/19

Conductor structure signal line

19x 0.13 mm

AWG signal line

24

Conductor cross section

2x 0.25 mm ² (Signal line)

Wire diameter incl. insulation

2.55 mm ±0.07 mm

External cable diameter

7.80 mm ±0.2 mm

Outer sheath, material

PUR

External sheath, color

red lilac RAL 4001

Conductor material

Tin-plated Cu litz wires

SAC-2P-M12MSB/10,0-910/M12FSB - Bus system cable



1507395

<https://www.phoenixcontact.com/us/products/1507395>

Material, filler	PP
Material wire insulation	Foam-Skin PP
Single wire, color	red, green
Overall twist	2 cores with 2 fillers to the core
Optical shield covering	85 %
Max. conductor resistance	$\leq 78.6 \Omega/\text{km}$
Insulation resistance	$\geq 5 \text{ G}\Omega \cdot \text{km}$
Wave impedance	$150 \Omega \pm 10 \%$ (3 MHz ... 20 MHz)
Cable capacity	nom. 30 pF/m
Nominal voltage, cable	300 V
Test voltage Core/Core	1500 V (50 Hz, 1 min.)
Test voltage Core/Shield	1500.00 V (50 Hz, 1 min.)
Smallest bending radius, fixed installation	40 mm
Smallest bending radius, movable installation	65 mm
Max. bending cycles	4000000 5000000
Shield attenuation	$\leq 0.049 \text{ dB/m}$ (at 16 MHz)
Halogen-free	in accordance with DIN VDE 0472 part 815 according to IEC 60754-1
Flame resistance	UL 1581, Section 1060 and UL 2556, Section 9.3 (FT1) UL 1581, Section 1100 and UL 2556, Section 9.1 (HFT/FT2) IEC 60332-1-2
Other resistance	Low adhesion
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -30 °C ... 70 °C (Cable, flexible installation) -20 °C ... 60 °C (for installation) -20 °C ... 60 °C (cable, drag chain applications)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com