

1513787

https://www.phoenixcontact.com/pc/products/1513787

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector front mounting, Universal, 8-position, Pin, straight, M12-Standard, coding: A, on free cable end, Front mounting, Pg9, Individual wires, cable length: 0.5 m, 0.25 mm^2 , TPE litz wire, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1239868

Your advantages

- · Preassembled with litz wires for immediate use
- · Customer-specific assemblies and litz wire lengths available
- · Sealed on the litz wire side for optimum leak-tightness
- For high transmission safety: shield connection to the housing with optional EMC nut

Commercial data

| Item number | 1513787 |
|--------------------------------------|--------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Product key | ABQCEE |
| Catalog page | Page 35 (C-2-2019) |
| GTIN | 4017918914677 |
| Weight per piece (including packing) | 29.23 g |
| Weight per piece (excluding packing) | 29.23 g |
| Customs tariff number | 85444290 |
| Country of origin | DE |



1513787

https://www.phoenixcontact.com/pc/products/1513787

Technical data

Notes

| Notes on operation | The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration. |
|--------------------|--|
| Order information: | Lock nut is included in the scope of delivery |
| General | Contact connection method: Crimp connection |

Mounting

| Mounting type | Front mounting Pg9 With locking nut |
|-----------------------|-------------------------------------|
| Assembly instructions | With locking nut |

Product properties

| Product type | Circular connectors (device side) |
|----------------------------|-----------------------------------|
| Application | Signal |
| Sensor type | Universal |
| Number of positions | 8 |
| No. of cable outlets | 1 |
| Shielded | no |
| Coding | A |
| Thread type | M12 |
| Insulation characteristics | |
| Overvoltage category | II |
| Degree of pollution | 3 |

Material specifications

| Flammability rating according to UL 94 | V0 |
|--|------------------------------|
| Seal material | NBR |
| Material of grip body | Zinc die-cast, nickel-plated |
| Contact material | CuZn |
| Contact surface material | Ni/Au |
| Contact carrier material | PA 66 |
| Material for screw connection | Zinc die-cast, nickel-plated |
| Conductor material | Tin-plated Cu litz wires |

Electrical properties

| Rated surge voltage | 0.8 kV |
|-----------------------|----------|
| Contact resistance | ≤ 3 mΩ |
| Insulation resistance | ≥ 100 MΩ |



1513787

https://www.phoenixcontact.com/pc/products/1513787

| Nominal voltage U _N | 30 V (AC) |
|--------------------------------|-----------|
| | 30 V (DC) |
| Nominal current I _N | 2 A |
| Max. conductor resistance | 80 mΩ/m |

Connection data

Conductor connection

| Connection method | Individual wires |
|-------------------------|-------------------------------|
| Contact connection type | Pin |
| Conductor cross section | 0.25 mm² |
| Tightening torque | 2 Nm 3 Nm (Installation-side) |

Mechanical properties

Mechanical data

| Insertion/withdrawal cycles | > 100 |
|-----------------------------|-------|

Connector

Connection 1

| Head design | Pin |
|-------------------|----------|
| Head cable outlet | straight |
| Head thread type | M12 |
| Head locking type | Standard |
| Coding | A |

Connection 2

| Head design free cable end |
|----------------------------|
|----------------------------|

Cable/line

| Cable length | 0.5 m |
|---------------------------------|--|
| Cable type | TPE litz wire |
| Signal type/category | Universal |
| Wire diameter incl. insulation | 1.15 mm ±0.07 mm |
| Single wire, color | brown, blue, white, gray, pink, green, yellow, red |
| Cable cross section | 0.25 mm² |
| Conductor material | Tin-plated Cu litz wires |
| Conductor structure signal line | 14x 0.15 mm |
| AWG signal line | 24 |
| Material wire insulation | TPE |
| Thickness, insulation | 0.21 mm (Core insulation) |
| Nominal voltage, cable | 300 V |
| Test voltage, cable | 2000 V AC |
| Cable resistance | ≤ 80 mΩ/m |



1513787

https://www.phoenixcontact.com/pc/products/1513787

| Cable insulation resistance | ≥ 20 MΩ*km |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C 85 °C (cable, fixed installation) |
| | -25 °C 85 °C (Cable, flexible installation) |

Environmental and real-life conditions

Ambient conditions

| Degree of protection | IP67 |
|---------------------------------|---|
| | IP67 |
| Ambient temperature (operation) | -25 °C 85 °C (Plug / socket) |
| | -40 °C 85 °C (without mechanical actuation) |
| | -25 °C 85 °C (Cable, flexible installation) |
| | -40 °C 85 °C (cable, fixed installation) |

Standards and regulations

M12

| Standard designation | M12 connector |
|--------------------------|-----------------|
| Standards/specifications | IEC 61076-2-101 |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com