

1519370

<https://www.phoenixcontact.com/pc/products/1519370>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bus system cable, CANopen[®], DeviceNet[™], 5-position, PUR halogen-free, red lilac RAL 4001, shielded (Tinned copper braided shield), free cable end, on Socket straight M12, coding: A, cable length: 0.5 m

Commercial data

Item number	1519370
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF1CKD
GTIN	4017918938710
Weight per piece (including packing)	54.5 g
Weight per piece (excluding packing)	51.5 g
Customs tariff number	85444290
Country of origin	PL

SAC-5P- 0,5-920/M12FS - Bus system cable



1519370

<https://www.phoenixcontact.com/pc/products/1519370>

Technical data

Product properties

Product type	Data cable preassembled
Sensor type	CANopen [®]
Number of positions	5
Shielded	yes

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Interfaces

Bus system	CANopen [®] /DeviceNet [™]
Signal type/category	CANopen [®]
	DeviceNet [™]

Signaling

Status display	No
Status display present	No

Electrical properties

Insulation resistance	≥ 100 MΩ
Nominal voltage U _N	48 V AC
	60 V DC
Nominal current I _N	4 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	-------

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

Connector

Connection 1

Type	free cable end
------	----------------

SAC-5P- 0,5-920/M12FS - Bus system cable



1519370

<https://www.phoenixcontact.com/pc/products/1519370>

Connection 2

Type	free cable end
------	----------------

Cable/line

Cable length	0.5 m
--------------	-------

CANopen[®]/DeviceNet[™], PUR, violet [920]

Dimensional drawing		
Cable weight	90 kg/km	
UL AWM Style	21198 (80°C/300 V)	
Number of positions	4	
Shielded	yes	
Cable type	CANopen [®] /DeviceNet [™] , PUR, violet [920]	
Conductor structure	2xAWG24/19+2xAWG22/19	
Conductor structure signal line	19x 0.13 mm	
AWG signal line	24	
Conductor cross section	2x 0.25 mm ² (Data cable)	
	2x 0.34 mm ² (Power supply)	
	1x 0.34 mm ² (Drain wire)	
Wire diameter incl. insulation	1.95 mm ±0.05 mm (Data cable)	
	1.4 mm ±0.05 mm (Power supply)	
External cable diameter	6.70 mm ±0.3 mm	
Outer sheath, material	PUR	
External sheath, color	red lilac RAL 4001	
Conductor material	Tin-plated Cu litz wires	
Material wire insulation	Foamed PE (Data cable)	
	PE (Power supply)	
Single wire, color	red-black, blue-white	
Twisted pairs	2 cores to the pair	
Type of pair shielding	Plastic-coated aluminum foil, aluminum side outside	
Overall twist	2 pairs around a drain wire in the center to the core	
Optical shield covering	80 %	
Insulation resistance	≥ 5 GΩ*km (Data cable)	
	≥ 5 GΩ*km (Power supply)	
Loop resistance	≤ 181.80 Ω/km (Data cable)	
	≤ 114.80 Ω/km (Power supply)	
Wave impedance	120 Ω ±10 % (with 1 MHz)	

SAC-5P- 0,5-920/M12FS - Bus system cable



1519370

<https://www.phoenixcontact.com/pc/products/1519370>

Cable capacity	nom. 40 nF/km (Data cable)
Nominal voltage, cable	≤ 300 V (Peak value, not for high-power applications)
Test voltage Core/Core	2000 V (50 Hz, 1 min.)
Test voltage Core/Shield	2000.00 V (50 Hz, 1 min.)
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	34 mm
Smallest bending radius, movable installation	67 mm
Max. bending cycles	5000000
Shield attenuation	≤ 22.9 dB/km (with 1 MHz)
	≤ 16.4 dB/km (At 500 kHz)
	≤ 9.5 dB/km (At 125 kHz)
Halogen-free	in accordance with DIN VDE 0472 part 815
	according to IEC 60754-1
Flame resistance	IEC 60332-1-2
	in accordance with ISO 6722-1 5.22 (UN ECE-R 118.01)
Other resistance	Low adhesion
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-30 °C ... 70 °C (Cable, flexible installation)
	-20 °C ... 60 °C (for installation)
	-20 °C ... 60 °C (cable, drag chain applications)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)
	-40 °C ... 80 °C (cable, fixed installation)
	-20 °C ... 75 °C (Cable, flexible installation)

SAC-5P- 0,5-920/M12FS - Bus system cable

1519370

<https://www.phoenixcontact.com/pc/products/1519370>


Drawings

Dimensional drawing



M12 x 1 socket, straight, shielded

Schematic diagram



Pin assignment M12 socket, 5-pos., A-coded, socket side view


SAC-5P- 0,5-920/M12FS - Bus system cable



1519370

<https://www.phoenixcontact.com/pc/products/1519370>

Circuit diagram



SAC-5P- 0,5-920/M12FS - Bus system cable



1519370

<https://www.phoenixcontact.com/pc/products/1519370>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1519370>



EAC-RoHS

Approval ID: RU D-DE.HB35.B.00387

SAC-5P- 0,5-920/M12FS - Bus system cable



1519370

<https://www.phoenixcontact.com/pc/products/1519370>

Classifications

ECLASS

ECLASS-11.0	27060307
ECLASS-12.0	27060307
ECLASS-13.0	27060307

ETIM

ETIM 8.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-5P- 0,5-920/M12FS - Bus system cable



1519370
<https://www.phoenixcontact.com/pc/products/1519370>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com