

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable



1519956
<https://www.phoenixcontact.com/us/products/1519956>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR/PVC, yellow, Plug straight M12, coding: A, on Socket angled M12, coding: A, cable length: 0.6 m

Commercial data

Item number	1519956
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF03
Product key	BF1CBA
GTIN	4017918945060
Weight per piece (including packing)	74.2 g
Weight per piece (excluding packing)	77.3 g
Customs tariff number	85444290
Country of origin	PL

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable



1519956

<https://www.phoenixcontact.com/us/products/1519956>

Technical data

Product properties

Product type	Sensor/actuator cable
Number of positions	3
No. of cable outlets	2
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Insulation resistance	$\geq 10 \text{ G}\Omega$
Nominal voltage U_N	250 V AC
	250 V DC
Nominal current I_N	4 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Signaling

Status display	No
Status display present	No

Connection data

Conductor connection

Tightening torque	0.4 Nm
-------------------	--------

Connector

Connection 1

Type	Plug straight M12
------	-------------------

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable



1519956

<https://www.phoenixcontact.com/us/products/1519956>

Number of positions	3
Coding type	A


Connection 2

Type	Socket angled M12
Number of positions	3
Coding type	A

Cable/line

Cable length	0.6 m
--------------	-------

PUR/PVC yellow [140]

Dimensional drawing		
Cable weight	37 kg/km	
Number of positions	3	
Shielded	no	
Cable type	PUR/PVC yellow [140]	
Conductor structure signal line	42x 0.10 mm	
AWG signal line	22	
Conductor cross section	0.34 mm ²	
Wire diameter incl. insulation	1.52 mm ±0.02 mm	
External cable diameter	5.20 mm ±0.2 mm	
Outer sheath, material	PUR	
External sheath, color	yellow	
Conductor material	Bare Cu litz wires	
Material wire insulation	PVC	
Single wire, color	brown, blue, black	
Thickness, insulation	≥ 0.23 mm (Core insulation)	
	≥ 0.38 mm (Outer cable sheath)	
	approx. 0.45 mm (Inner sheath)	
Overall twist	3 wires, twisted	
Max. conductor resistance	max. 57.3 Ω/km (at 20 °C)	
Insulation resistance	≥ 100 MΩ*km (at 20 °C)	
Nominal voltage, cable	300 V	
Test voltage	2500 V	
Smallest bending radius, fixed installation	52 mm	
Smallest bending radius, movable installation	52 mm	
Max. bending cycles	2000000	

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable



1519956
<https://www.phoenixcontact.com/us/products/1519956>

Ambient temperature (operation)	-25 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)
	-25 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable

1519956

<https://www.phoenixcontact.com/us/products/1519956>

Drawings

Dimensional drawing




M12 x 1 socket, angled

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable

1519956


<https://www.phoenixcontact.com/us/products/1519956>

Schematic diagram



Pin assignment M12 plug, 4-pos., A-coded, view plug side

Dimensional drawing




Plug M12 x 1, Y distributor

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable

1519956

<https://www.phoenixcontact.com/us/products/1519956>

Schematic diagram



Pin assignment M12 socket, 3-pos., A-coded, view female side

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable



1519956
<https://www.phoenixcontact.com/us/products/1519956>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1519956>

	UL Listed Approval ID: FILE E 221474			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	300 V	4 A	-	-

	cUL Listed Approval ID: FILE E 221474			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	300 V	4 A	-	-

	EAC-RoHS Approval ID: RU D-DE.HB35.B.00387			

cULus Listed				
---------------------	--	--	--	--

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable



1519956

<https://www.phoenixcontact.com/us/products/1519956>

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 8.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-3P-M12Y/2X0,6-140/M12FR - Sensor/actuator cable



1519956
<https://www.phoenixcontact.com/us/products/1519956>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com