

SAC-4P-MICFS/ 5,0-PUR - Sensor/actuator cable



1527171

<https://www.phoenixcontact.com/us/products/1527171>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 4-position, PUR/PVC, black-gray RAL 7021, free cable end, on Socket straight 1/2"-20UNF, coding: C, cable length: 5 m

Commercial data

Item number	1527171
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF09
Product key	BF1ECA
GTIN	4046356071888
Weight per piece (including packing)	222.22 g
Weight per piece (excluding packing)	222.22 g
Customs tariff number	85444290
Country of origin	US

SAC-4P-MICFS/ 5,0-PUR - Sensor/actuator cable



1527171

<https://www.phoenixcontact.com/us/products/1527171>

Technical data

Notes

Trade restriction

CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
---------	--

Product properties

Product type	Sensor/actuator cable
Number of positions	4
No. of cable outlets	1
Shielded	no
Coding	C

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated
Outer sheath, material	PUR
Conductor material	Bare Cu litz wires

Electrical properties

Insulation resistance	$\geq 10 \text{ M}\Omega$
Nominal voltage U_N	250 V AC
	250 V DC
Nominal current I_N	4 A
Max. conductor resistance	58 Ω/km

Mechanical properties

Mechanical data

Max. bending cycles	2000000
---------------------	---------

Signaling

Status display	No
Status display present	No

SAC-4P-MICFS/ 5,0-PUR - Sensor/actuator cable



1527171

<https://www.phoenixcontact.com/us/products/1527171>

Connector

Connection 1

Type	free cable end
------	----------------


Connection 2

Type	Socket straight 1/2"-20UNF
Number of positions	4
Coding type	C

Cable/line

Cable length	5 m
--------------	-----

PUR/PVC black [350]

Dimensional drawing		
Cable weight	39 kg/km	
UL AWM Style	20549	
Number of positions	4	
Shielded	no	
Cable type	PUR/PVC black [350]	
Conductor structure signal line	42x 0.10 mm	
AWG signal line	22	
Conductor cross section	0.34 mm²	
Wire diameter incl. insulation	1.5 mm ±0.05 mm	
External cable diameter	5.20 mm ±0.2 mm	
Outer sheath, material	PUR	
External sheath, color	black-gray RAL 7021	
Conductor material	Bare Cu litz wires	
Material wire insulation	PVC	
Single wire, color	green, red/black, red/white, red	
Thickness, insulation	approx. 0.30 mm (Core insulation)	
	≥ 0.38 mm (Outer cable sheath)	
	approx. 0.35 mm (Inner sheath)	
Max. conductor resistance	max. 58 Ω/km (at 20 °C)	
Insulation resistance	≥ 1 GΩ*km (at 20 °C)	
Nominal voltage, cable	≤ 300 V	
Test voltage	≥ 3000 V	

SAC-4P-MICFS/ 5,0-PUR - Sensor/actuator cable



1527171

<https://www.phoenixcontact.com/us/products/1527171>

Smallest bending radius, fixed installation	52 mm
Smallest bending radius, movable installation	52 mm
Max. bending cycles	2000000
Flame resistance	in accordance with DIN UL-Style 20549
Ambient temperature (operation)	-25 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)
	-25 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

SAC-4P-MICFS/ 5,0-PUR - Sensor/actuator cable




1527171

<https://www.phoenixcontact.com/us/products/1527171>


Drawings

Schematic diagram



Pin assignment 1/2"-20UNF socket, 4-pos., view female side

Dimensional drawing



1/2"-20UNF socket, straight

SAC-4P-MICFS/ 5,0-PUR - Sensor/actuator cable



1527171

<https://www.phoenixcontact.com/us/products/1527171>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1527171>

	UL Listed Approval ID: FILE E 221474			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	300 V	4 A	-	-

	cUL Listed Approval ID: FILE E 221474			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	300 V	4 A	-	-

cULus Listed

SAC-4P-MICFS/ 5,0-PUR - Sensor/actuator cable



1527171

<https://www.phoenixcontact.com/us/products/1527171>

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%