

# Specifications



## Eaton 152864

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Palm-tree shape, 60 mm, Non-illuminated, Pull-to-release function, Red, yellow

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton
<b>CATALOG NUMBER</b>	152864
<b>MODEL CODE</b>	M22-PV60P
<b>EAN</b>	4015081496426
<b>PRODUCT LENGTH/DEPTH</b>	67 mm
<b>PRODUCT HEIGHT</b>	60 mm
<b>PRODUCT WIDTH</b>	60 mm
<b>PRODUCT WEIGHT</b>	0.051 kg
<b>CERTIFICATIONS</b>	IEC/EN 60947 VDE 0660 DNV GL LR
<b>GLOBAL CATALOG</b>	152864



Powering Business Worldwide

## Product specifications

<b>TYPE</b>	Controlled stop pushbutton/emergency-stop button
<b>ACTUATOR COLOR</b>	Red
<b>FEATURES</b>	Tamper-proof (according to ISO 13850, EN 418)
<b>ACTUATOR FUNCTION</b>	Pull-to-release Switching function latching
<b>10.10 TEMPERATURE RISE</b>	Not applicable.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Please enquire
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.

## Resources

<b>CATALOGS</b>	<a href="#">eaton-rmq-titan-brochure-br047004en-en-us.pdf</a>  <a href="#">Flip catalog - Product Range Catalog - Command and indication</a>  <a href="#">eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf</a>
<b>CERTIFICATION REPORTS</b>	<a href="#">000Z425</a>  <a href="#">eaton-emergency-stop-emergency-switching-off-pushbutton-declaration-of-conformity-eu250649en.pdf</a>  <a href="#">DA-DC-00004975.pdf</a>  <a href="#">DA-DC-00004971.pdf</a>
<b>DECLARATIONS OF CONFORMITY</b>	
<b>DRAWINGS</b>	<a href="#">eaton-operating-m22-dimensions-017.eps</a>  <a href="#">eaton-operating-m22-dimensions-015.eps</a>  <a href="#">eaton-general-m22-standards.eps</a>  <a href="#">eaton-operating-m22-3d-drawing-006.eps</a>  <a href="#">eaton-general-m22-symbol.eps</a>  <a href="#">eaton-general-approval-m22-symbol.eps</a>  <a href="#">eaton-operating-button-symbol-006.eps</a>
<b>ECAD MODEL</b>	<a href="#">ETN.152864.edz</a>
<b>FLYERS</b>	<a href="#">eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">IL04716002Z</a>  <a href="#">IL04716005Z.pdf</a>
<b>INSTALLATION VIDEOS</b>	<a href="#">RMQ Flat Design</a>
<b>MCAD MODEL</b>	<a href="#">DA-CD-not aus 60 schaltanzeige</a>  <a href="#">DA-CS-not aus 60 schaltanzeige</a>

<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>OPERATING FREQUENCY</b>	600 Operations/h
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>CONNECTION TO SMARTWIRE-DT</b>	No
<b>BASE COLOR</b>	Yellow
<b>ACTUATING FORCE</b>	50 N
<b>ACTUATOR DIAMETER</b>	60 mm
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	80 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	40 °C
<b>DIAMETER CAP</b>	60 mm
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>FORCE FOR POSITIVE OPENING - MIN</b>	0 N

## MULTIMEDIA

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

[RMQ small E-Stop emergency-stop button](#)

[MCI MultiColor Light Indicator RMQ compact solution](#)

[MCI Multicolor Light Indicator M22 with SmartWire-DT](#)

## SALES NOTES

[eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf](#)

<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
<b>OPENING DIAMETER</b>	22.5 mm
<b>OPENING HEIGHT</b>	0 mm
<b>RAL-NUMBER</b>	3000
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
<b>ILLUMINATION</b>	Non-illuminated
<b>BEZEL COLOR</b>	Other
<b>SHOCK RESISTANCE</b>	Mechanical, According to IEC/EN 60068-2-27 50 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
<b>BEZEL MATERIAL</b>	Other
<b>DESIGN</b>	Palm-tree shaped Classical
<b>MOUNTING POSITION</b>	As required
<b>DEGREE OF PROTECTION</b>	NEMA 4X IP66
<b>FRONT ELEMENT TYPE</b>	High
<b>LENS TYPE</b>	Round
<b>LIFESPAN, MECHANICAL</b>	100,000 Operations
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>WIDTH OPENING</b>	0 mm
<b>PRODUCT CATEGORY</b>	RMQ-Titan
<b>SIZE</b>	Front dimensions: 22 x 22 mm
<b>SUPPLY VOLTAGE LAMP</b>	0 V
<b>SUITABLE FOR</b>	Emergency stop
<b>UNLOCKING METHOD</b>	Pull-release

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

