

1529755

https://www.phoenixcontact.com/us/products/1529755

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector front mounting, INTERBUS (16 Mbps), 5-position, PUR halogen-free, green RAL 6017, shielded, Socket, straight, M12, coding: B, on free cable end, Front mounting, M16 x 1.5, Cable connection, cable length: 1 m, INTERBUS, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1239918

Your advantages

- · Preassembled with cables in various standard lengths for immediate use
- · Customer-specific assemblies and cable lengths can be supplied
- · Sealed on the cable side for optimum tightness of seal
- · Cable designs for all common networks and fieldbuses
- · For high transmission safety: shield connection to the housing with optional EMC nut

Commercial data

Item number	1529755
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB25
Product key	ABQDEG
Catalog page	Page 425 (C-2-2019)
GTIN	4017918982669
Weight per piece (including packing)	97.3 g
Weight per piece (excluding packing)	96 g
Customs tariff number	85444290
Country of origin	DE



1529755

https://www.phoenixcontact.com/us/products/1529755

Technical data

Notes

	connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Order information:	Lock nut is included in the scope of delivery
General	Contact connection method: Crimp connection

Safety note

Safety note

WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- WARNING: Commission properly functioning products only.
 The products must be regularly inspected for damage.
 Decommission defective products immediately. Replace damaged products. Repairs are not possible.
- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
- The products are suitable for applications in plant, controller, and electrical device engineering.
- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductive connector housings must be grounded
- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
- Observe the corresponding technical data. You will find information:
- o On the product
- o On the packing label
- o In the supplied documentation
- o Online at phoenixcontact.com/products under the product
- · Only use tools recommended by Phoenix Contact
- Use a protective cap to protect connectors that are not in use.



1529755

https://www.phoenixcontact.com/us/products/1529755

	The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
	 Ensure that the protective or functional ground has been properly connected.
	 VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
	 The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).
ounting	
Mounting type	Front mounting M16 x 1.5 With locking nut
Assembly note	With locking nut
roduct properties	
Product type	Circular connectors (device side)
Sensor type	INTERBUS
Number of positions	5
No. of cable outlets	1
Shielded	yes
Coding	В
Thread type	M12
Data management status	
Article revision	11
Insulation characteristics	
Overvoltage category	II II
Degree of pollution	3
aterial specifications	
Flammability rating according to UL 94	
	V0
Seal material	V0 NBR
Seal material Contact material	
	NBR
Contact material	NBR CuZn
Contact material Contact surface material	NBR CuZn Ni/Au
Contact material Contact surface material Contact carrier material	NBR CuZn Ni/Au PA 6.6
Contact material Contact surface material Contact carrier material Material for screw connection	NBR CuZn Ni/Au PA 6.6 Brass, nickel-plated
Contact material Contact surface material Contact carrier material Material for screw connection Outer sheath, material lectrical properties	NBR CuZn Ni/Au PA 6.6 Brass, nickel-plated
Contact material Contact surface material Contact carrier material Material for screw connection Outer sheath, material	NBR CuZn Ni/Au PA 6.6 Brass, nickel-plated PUR
Contact material Contact surface material Contact carrier material Material for screw connection Outer sheath, material lectrical properties Rated surge voltage	NBR CuZn Ni/Au PA 6.6 Brass, nickel-plated PUR



1529755

https://www.phoenixcontact.com/us/products/1529755

	60 V DC
Nominal current I _N	4 A (Plug/socket in accordance with IEC 61076-2-101, cable technical data is to be observed)
Test voltage	2500 V
Transmission medium	Copper

Connection data

Conductor connection

Connection method	Cable connection
Contact connection type	Socket
Tightening torque	3 Nm 4 Nm (Installation-side)

Mechanical properties

Mechanical data

Wechanical data	
Insertion/withdrawal cycles	> 100

Connector

Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Coding	В

Connection 2

Head design fr	ee cable end
----------------	--------------

Cable/line

Cable length	1 m

INTERBUS [900]

Dimensional drawing



Cable weight	70 kg/km
Number of positions	6
Shielded	yes
Cable type	INTERBUS [900]
Conductor structure	3 x 2 x 0.22 mm ²



1529755

https://www.phoenixcontact.com/us/products/1529755

Signal speed	0.66 c
Conductor structure signal line	32x 0.10 mm
AWG signal line	24
Conductor cross section	3x 2x 0.22 mm²
External cable diameter	8.00 mm
Outer sheath, material	PUR
External sheath, color	may green RAL 6017
Conductor material	Bare Cu litz wires
Material wire insulation	PE
Single wire, color	green-yellow, white-brown, gray-pink
Twisted pairs	2 cores to the pair
Overall twist	3 pairs to the core
Insulation resistance	≥ 5 GΩ*km
Coupling resistance	< 250.00 mΩ/m (at 30 MHz)
Loop resistance	≤ 159.80 Ω/km
Wave impedance	120 Ω ±20 % (at 64 kHz)
	100 Ω ±15 % (with 1 MHz)
Cable capacity	≤ 60 nF/km (At 800 Hz)
Nominal voltage, cable	250 V (Peak value, not for high-power applications)
Test voltage Core/Core	1500 V _{rms}
Test voltage Core/Shield	1000.00 V _{rms}
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	15 x D
Smallest bending radius, fixed installation	60 mm
Smallest bending radius, movable installation	120 mm
Max. bending cycles	5000000
Bending radius	120 mm
Traversing path	10 m
Traversing rate	1.6 m/s
Acceleration	3.2 m/s ²
Near end crosstalk attenuation (NEXT)	≥ 61 dB (at 772 kHz)
	≥ 59 dB (with 1 MHz)
	≥ 55 dB (at 2 MHz)
	≥ 50 dB (at 4 MHz)
	≥ 46 dB (at 8 MHz)
	≥ 44 dB (at 10 MHz)
	≥ 41 dB (at 16 MHz)
	≥ 40 dB (at 20 MHz)
Shield attenuation	≤ 15 dB/km (at 256 kHz)
	≤ 24 dB/km (at 772 kHz)
	≤ 27 dB/km (with 1 MHz)
	≤ 52 dB/km (at 4 MHz)



1529755

https://www.phoenixcontact.com/us/products/1529755

	≤ 84 dB/km (at 10 MHz)
	≤ 112 dB/km (at 16 MHz)
	≤ 119 dB/km (at 20 MHz)
Flame resistance	according to VDE 0472, Part 4, test type B
	according to IEC 60332-1
Ambient temperature (operation)	-40 °C 80 °C (cable, fixed installation)
	-30 °C 70 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
	IP65/IP67
Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)
	-40 °C 85 °C (without mechanical actuation)

Standards and regulations

M12

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101




1529755


https://www.phoenixcontact.com/us/products/1529755

Drawings

Circuit diagram



Schematic diagram



Pin assignment M12 socket, 5-pos., B-coded, female side



1529755

https://www.phoenixcontact.com/us/products/1529755

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1529755

cUL Recognized Approval ID: E221474-20220907				
	Nominal voltage U_N	Nominal current I _N	Cross section AWG	Cross section mm ²
	60 V	1.5 A	-	-

71	UL Recognized Approval ID: E221474-20220907				
		Nominal voltage $\mathbf{U}_{\mathbf{N}}$	Nominal current I _N	Cross section AWG	Cross section mm ²
		60 V	2 A	-	-

cULus Recognized



1529755

https://www.phoenixcontact.com/us/products/1529755

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27440103	
	ECLASS-12.0	27440103	
	ECLASS-13.0	27440103	
ETIM			
	ETIM 9.0	EC003570	
UNSPSC			

39121400



1529755

https://www.phoenixcontact.com/us/products/1529755

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	492e5f97-4bb9-4e6d-b89b-e86b27bf568c

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com