

1530281
<https://www.phoenixcontact.com/gb/products/1530281>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR, black RAL 9005, Plug straight M5, coding: A, on free cable end, cable length: 5 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

Item number	1530281
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF1ABA
Product key	BF1ABA
Catalog page	Page 190 (C-2-2017)
GTIN	4046356024082
Weight per piece (including packing)	66.88 g
Weight per piece (excluding packing)	66 g
Customs tariff number	85444290
Country of origin	DE

SAC-3P-M5MS/ 5,0-PUR - Sensor/actuator cable



1530281

<https://www.phoenixcontact.com/gb/products/1530281>

Technical data

Product properties

Product type	Sensor/actuator cable
Application	Standard
Number of positions	3
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Material of grip body	PUR
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PUR
Material for screw connection	Brass, nickel-plated

Electrical properties

Insulation resistance	$\geq 10 \text{ G}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	1 A
Test voltage	1750 V

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Signaling

Status display	No
Status display present	No

Connector

Connection 1

Type	Plug straight M5
Number of positions	3
Coding type	A

Connection 2

Type	free cable end
------	----------------

SAC-3P-M5MS/ 5,0-PUR - Sensor/actuator cable




1530281

<https://www.phoenixcontact.com/gb/products/1530281>

Cable/line

Cable length	5 m
--------------	-----

PUR/PVC black [350]

Dimensional drawing	
Cable weight	12.9 kg/km
Number of positions	3
Shielded	no
Cable type	PUR/PVC black [350]
Conductor structure signal line	18x 0.10 mm
AWG signal line	26
Conductor cross section	3x 0.14 mm ² (Signal line)
Wire diameter incl. insulation	1.1 mm
External cable diameter	3.00 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, black
Overall twist	3 wires, twisted
Max. conductor resistance	148 Ω/km
Insulation resistance	100 MΩ*km
Nominal voltage, cable	250 V
Test voltage	800 V _{rms}
Smallest bending radius, fixed installation	8 mm
Smallest bending radius, movable installation	15 mm
Ambient temperature (operation)	-15 °C ... 80 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 IP67 IP68
Ambient temperature (operation)	-25 °C ... 80 °C (Plug / socket)

SAC-3P-M5MS/ 5,0-PUR - Sensor/actuator cable



1530281

<https://www.phoenixcontact.com/gb/products/1530281>

Standards and regulations

Standard designation	M5 connector
Standards/specifications	IEC 61076-2-105

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk