

1530485
<https://www.phoenixcontact.com/us/products/1530485>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 4-position, PUR, black RAL 9005, free cable end, on Socket straight M5, coding: A

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

Item number	1530485
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	B06
Product key	BF1ACA
Catalog page	Page 190 (C-2-2017)
GTIN	4046356024280
Weight per piece (including packing)	83.4 g
Weight per piece (excluding packing)	83.4 g
Customs tariff number	85444290
Country of origin	DE

SAC-4P- 5,0-PUR/M5FS - Sensor/actuator cable



1530485

<https://www.phoenixcontact.com/us/products/1530485>

Technical data

Product properties

Product type	Sensor/actuator cable
Application	Standard
Number of positions	4
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Seal material	NBR
Material of grip body	PUR
Contact material	CuSn
Contact surface material	Au
Contact carrier material	PUR
Material for screw connection	Brass, nickel-plated

Electrical properties

Insulation resistance	$\geq 10 \text{ G}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	1 A
Test voltage	1750 V

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Signaling

Status display	No
Status display present	No

Connector

Connection 1

Type	free cable end
------	----------------

Connection 2

Type	Socket straight M5
Number of positions	4

SAC-4P- 5,0-PUR/M5FS - Sensor/actuator cable




1530485

<https://www.phoenixcontact.com/us/products/1530485>

Coding type	A
-------------	---

Cable/line

PUR/PVC black [350]

Dimensional drawing	
Number of positions	4
Shielded	no
Cable type	PUR/PVC black [350]
Conductor structure signal line	18x 0.10 mm
AWG signal line	26
Conductor cross section	4x 0.14 mm ² (Signal line)
Wire diameter incl. insulation	0.92 mm ±0.02 mm
External cable diameter	3.50 mm ±0.1 mm
Outer sheath, material	PUR
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, white, blue, black
Overall twist	4 wires, twisted
Max. conductor resistance	148 Ω/km
Insulation resistance	100 MΩ*km
Nominal voltage, cable	100 V
Test voltage	800 V _{rms}
Smallest bending radius, fixed installation	9 mm
Smallest bending radius, movable installation	18 mm
Ambient temperature (operation)	-15 °C ... 80 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 IP67 IP68
Ambient temperature (operation)	-25 °C ... 80 °C (Plug / socket)

Standards and regulations

SAC-4P- 5,0-PUR/M5FS - Sensor/actuator cable



1530485

<https://www.phoenixcontact.com/us/products/1530485>

Standard designation	M5 connector
Standards/specifications	IEC 61076-2-105

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com