

SAC-3P- 5,0-PUR/M5FR - Sensor/actuator cable



1530524

<https://www.phoenixcontact.com/us/products/1530524>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR, black RAL 9005, free cable end, on Socket angled M5, coding: A

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

Item number	1530524
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	B06
Product key	BF1ABA
Catalog page	Page 190 (C-2-2017)
GTIN	4046356024327
Weight per piece (including packing)	66.9 g
Weight per piece (excluding packing)	66 g
Customs tariff number	85444290
Country of origin	DE

SAC-3P- 5,0-PUR/M5FR - Sensor/actuator cable



1530524

<https://www.phoenixcontact.com/us/products/1530524>

Technical data

Product properties

Product type	Sensor/actuator cable
Application	Standard
Number of positions	3
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Seal material	NBR
Material of grip body	PUR
Contact material	CuSn
Contact surface material	Au
Contact carrier material	PUR
Material for screw connection	Brass, nickel-plated

Electrical properties

Insulation resistance	$\geq 10 \text{ G}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	1 A
Test voltage	1750 V

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Signaling

Status display	No
Status display present	No

Connector

Connection 1

Type	free cable end
------	----------------

Connection 2

Type	Socket angled M5
Number of positions	3

SAC-3P- 5,0-PUR/M5FR - Sensor/actuator cable



1530524

<https://www.phoenixcontact.com/us/products/1530524>


Coding type

A

Cable/line

PUR/PVC black [350]

Dimensional drawing



Cable weight

12.9 kg/km

Number of positions

3

Shielded

no

Cable type

PUR/PVC black [350]

Conductor structure signal line

18x 0.10 mm

AWG signal line

26

Conductor cross section

3x 0.14 mm² (Signal line)

Wire diameter incl. insulation

1.1 mm

External cable diameter

3.00 mm ±0.2 mm

Outer sheath, material

PUR

External sheath, color

black RAL 9005

Conductor material

Bare Cu litz wires

Material wire insulation

PVC

Single wire, color

brown, blue, black

Overall twist

3 wires, twisted

Max. conductor resistance

148 Ω/km

Insulation resistance

100 MΩ*km

Nominal voltage, cable

250 V

Test voltage

800 V_{rms}

Smallest bending radius, fixed installation

8 mm

Smallest bending radius, movable installation

15 mm

Ambient temperature (operation)

-15 °C ... 80 °C (cable, fixed installation)

-5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection

IP65

IP67

IP68

Ambient temperature (operation)

-25 °C ... 80 °C (Plug / socket)

SAC-3P- 5,0-PUR/M5FR - Sensor/actuator cable



1530524

<https://www.phoenixcontact.com/us/products/1530524>

Standards and regulations

Standard designation	M5 connector
Standards/specifications	IEC 61076-2-105

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com