

1552311

https://www.phoenixcontact.com/us/products/1552311

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 5-position, Pin, straight, M12-SPEEDCON, coding: A, Rear mounting, Pg9, Solder pins, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1240014

## Your advantages

- Easy PCB assembly: one-piece connectors for wave soldering
- · All standard pin assignments and codings for signal, data, and power transmission with a uniform design-in design
- · SPEEDCON fast locking system reduces cabling times

## Commercial data

Item number	1552311
Packing unit	20 pc
Minimum order quantity	20 pc
Note	Made to order (non-returnable)
Sales key	AB26
Product key	ABQEGL
Catalog page	Page 246 (C-2-2013)
GTIN	4046356162166
Weight per piece (including packing)	13.89 g
Weight per piece (excluding packing)	13.89 g
Customs tariff number	85366990
Country of origin	DE



1552311

https://www.phoenixcontact.com/us/products/1552311

## Technical data

#### Notes

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Order information:	Lock nut is included in the scope of delivery

### Mounting

Mounting type	Rear mounting Pg9 With flat nut
Assembly note	With flat nut

### Product properties

Product type	Circular connectors (device side)
Number of positions	5
Shielded	no
Coding	A
Thread type	M12
Insulation characteristics	
Overvoltage category	II

## Dimensions

Length of the solder pin	12 mm
	12 mm

3

## Material specifications

Degree of pollution

Flammability rating according to UL 94	V0
Seal material	NBR
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated

### Electrical properties

Rated surge voltage	1.5 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U <sub>N</sub>	60 V
Nominal current I <sub>N</sub>	4 A



1552311

https://www.phoenixcontact.com/us/products/1552311

#### Connection data

#### Conductor connection

Connection method	Solder pins
Contact connection type	Pin
Tightening torque	2 Nm 3 Nm (Installation-side)

### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	> 100

#### Connector

#### Connection 1

Head design	Pin
Head cable outlet	straight
Head thread type	M12
Head locking type	SPEEDCON
Coding	A

#### Cable/line

Ambient temperature (operation)	-40 °C 85 °C (cable, fixed installation)
	-25 °C 85 °C (Cable, flexible installation)

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP67 (When plugged in)
	IP65 (When plugged in)
	IP65/IP67
Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)
	-40 °C 85 °C (without mechanical actuation)
	-25 °C 85 °C (Cable, flexible installation)
	-40 °C 85 °C (cable, fixed installation)

# Standards and regulations

#### M12


····-	
Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101



1552311

https://www.phoenixcontact.com/us/products/1552311

# Drawings



Pin assignment M12 male connector, 5-pos., A-coded, male side



1552311

https://www.phoenixcontact.com/us/products/1552311

# Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1552311

c <b>911</b> us	cULus Recognized Approval ID: E221474-20140616			
	Nominal voltage $U_N$	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
	60 V	4 A	-	-

<b>71</b>	<b>UL Recognized</b> Approval ID: E118976-2	0100522			
		Nominal voltage $U_N$	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
		60 V	4 A	22 - 22	-



1552311

https://www.phoenixcontact.com/us/products/1552311

## Classifications

### **ECLASS**

	ECLASS-11.0	27440102
	ECLASS-12.0	27440116
	ECLASS-13.0	27440116
ETIM		
	ETIM 9.0	EC002635
UNSPSC		
	UNSPSC 21.0	39121400



1552311

https://www.phoenixcontact.com/us/products/1552311

# Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	2bfb673e-1e1b-4872-9900-bc088f555c2d



1552311

https://www.phoenixcontact.com/us/products/1552311

### Accessories

SACC-PG9-SEAL CLM - Flat gasket

1556320

https://www.phoenixcontact.com/us/products/1556320

Pg9 flat gasket, for M12 flush-type connectors with Pg9 fastening thread



### PROT-M12 FS - Sealing cap

1560251

https://www.phoenixcontact.com/us/products/1560251



M12 sealing cap for unoccupied M12 plugs of the sensor/actuator cable, flush-type plugs and I/O devices in the field



1552311

https://www.phoenixcontact.com/us/products/1552311

### PROT-M12 FS-M - Sealing cap

1430488

https://www.phoenixcontact.com/us/products/1430488



M12 metal sealing cap for unoccupied M12 plugs of the sensor/actuator cable, flush-type plugs and I/O devices in the field

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com