


DC-B 6-H-80/O2STM20S-M - Housing



1581124

<https://www.phoenixcontact.com/us/products/1581124>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DUPLICON, aluminum stackable housing for DUPLICON contact inserts, type B6, IP67 degree of protection, with two locking latches, seal and two M20 cable screw connection threads (without cable gland), angled outlet

Commercial data

Item number	1581124
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	B10
Product key	BF7BAB
Catalog page	Page 662 (C-4-2015)
GTIN	4046356428026
Weight per piece (including packing)	290.3 g
Weight per piece (excluding packing)	290.3 g
Customs tariff number	85389099
Country of origin	SI

DC-B 6-H-80/O2STM20S-M - Housing

1581124

<https://www.phoenixcontact.com/us/products/1581124>




Technical data

Product properties

Housing type	Sleeve housing
Type	DC-B6
Type of the screw connection	With 2x M20 thread
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Height	37 mm

Material specifications

Color	pearl gray
Material Housing	die-cast aluminum
Seal material	NBR
Housing material	die-cast aluminum
Locking latch material	Stainless steel

Mechanical properties

Mechanical data	
Type of the screw connection	With 2x M20 thread
Locking type	Latch
Insertion/withdrawal cycles	≥ 100

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP65
	IP66
	IP67
	IP65/IP66/IP67
Ambient temperature (operation)	-40 °C ... 125 °C
Ambient temperature (storage/transport)	-40 °C ... 125 °C


DC-B 6-H-80/O2STM20S-M - Housing

1581124

<https://www.phoenixcontact.com/us/products/1581124>



Drawings



Dimensional drawing

DC-B 6-H-80/O2STM20S-M - Housing



1581124

<https://www.phoenixcontact.com/us/products/1581124>

Classifications

UNSPSC

UNSPSC 21.0	31261501
-------------	----------

Environmental product compliance

China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

DC-B 6-H-80/O2STM20S-M - Housing



1581124

<https://www.phoenixcontact.com/us/products/1581124>

Accessories

DC-B 6-A-HD-G - Seal

1602326

<https://www.phoenixcontact.com/us/products/1602326>

DUPLICON, profile gasket for stackable housing, made of conductive EPDM



EML (26,5X12)R SR - Label

0816854

<https://www.phoenixcontact.com/us/products/0816854>



Label, Roll, silver, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: 26.5 x 12 mm, Number of individual labels: 2500

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com