

Specifications

Photo is representative

Eaton 158253

Eaton Moeller® series PKZM4 Motor-protective circuit-breaker, Ir= 32 - 40 A, Screw terminals, Terminations: IP00 PKZM4-40/AK

General specifications

PRODUCT NAME	Eaton Moeller® series PKZM4 Motor-protective circuit-breaker
CATALOG NUMBER	158253
EAN	4015081548415
PRODUCT LENGTH/DEPTH	175 mm
PRODUCT HEIGHT	140 mm
PRODUCT WIDTH	55 mm
PRODUCT WEIGHT	1.25 kg
CERTIFICATIONS	UL File No.: E36332 CSA CSA Class No.: 3211-05 CE CSA File No.: 165628 CSA-C22.2 No. 60947-4-1-14 IEC/EN 60947-4-1 IEC/EN 60947 UL Category Control No.: NLRV VDE 0660 UL UL 60947-4-1
MODEL CODE	PKZM4-40/AK

Features & Functions

ACTUATOR TYPE	Turn button
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FUNCTIONS	Motor protection Phase failure sensitive
NUMBER OF POLES	Three-pole

General

EXPLOSION SAFETY CATEGORY FOR DUST	ATEX dust-ex-protection, PTB 10, ATEX 3012, Ex II(2) G
LIFESPAN, ELECTRICAL	30,000 operations (at 400V, AC-3)
LIFESPAN, MECHANICAL	30,000 Operations (Main conducting paths)
MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.
OPERATING FREQUENCY	40 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Motor protective circuit breaker
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
SUITABLE FOR	Also motors with efficiency class IE3 Branch circuit: Manual type E if used with terminal, or suitable for group installations, (UL/CSA)
TEMPERATURE COMPENSATION	-25 - 55 °C, Operating range ≤ 0.25 %/K, residual error for T > 40° -5 - 40 °C to IEC/EN 60947, VDE 0660

Climatic environmental conditions

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

RATED FREQUENCY - MIN	50 Hz
RATED FREQUENCY - MAX	60 Hz
RATED OPERATIONAL POWER AT AC-3, 220/230 V, 50 HZ	11 kW
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	20 kW
RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
RATED UNINTERRUPTED CURRENT (IU)	40 A

Terminal capacities

TERMINAL CAPACITY (SOLID/STRANDED AWG)	14 - 2
STRIPPING LENGTH (MAIN CABLE)	14 mm
TIGHTENING TORQUE	3.3 Nm, Screw terminals, Main cable

Short-circuit rating

SHORT-CIRCUIT CURRENT	60 kA DC, up to 250 V DC, Main conducting paths
SHORT-CIRCUIT CURRENT RATING (GROUP PROTECTION)	600 A, 600 V High Fault, max. Fuse, SCCR (UL/CSA) 42 kA, 600 V High Fault, CB, SCCR (UL/CSA) 600 A, 600 V High Fault, max. CB, SCCR (UL/CSA) 42 kA, 600 V High Fault, Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT CURRENT RATING (TYPE E)	Accessories required BK50/3-PKZ4-E 25 kA, 600 Y/347 V, SCCR (UL/CSA) 65 kA, 240 V, SCCR (UL/CSA) 65 kA, 480 Y/277 V, SCCR (UL/CSA)
SHORT-CIRCUIT RELEASE	Basic device fixed 15.5 x lu ± 20% tolerance 620 A, I _{rm}

Motor rating

ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE	3 HP
---	------

ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE	10 HP
---	-------

ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE	7.5 HP
---	--------

ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	30 HP
---	-------

ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE	30 HP
---	-------

Trip blocks

OVERLOAD RELEASE CURRENT SETTING - MIN	32 A
---	------

OVERLOAD RELEASE CURRENT SETTING - MAX	40 A
---	------

TRIPPING CHARACTERISTIC	Overload trigger: tripping class 10 A
----------------------------	--

Communication

CONNECTION	Screw terminals
------------	-----------------

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	20.7 W
---	--------

HEAT DISSIPATION CAPACITY PDISS	0 W
------------------------------------	-----

HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	6.9 W
--	-------

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	40 A
---	------

STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
--	-----

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
--------------------------------	---

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
--	---

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
---	---

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
--	---

10.2.4 RESISTANCE TO	Meets the product
----------------------	-------------------

ULTRA-VIOLET (UV) RADIATION	standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL
FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

BROCHURES

[eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf](#)

CATALOGUES

[eaton-switching-and-protecting-motors-product-range-catalog-ca034001en-en-us.pdf](#)

[Product Range Catalog Switching and protecting motors](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

CHARACTERISTIC CURVE

[eaton-manual-motor-starters-tripping-characteristic-pkzm4-characteristic-curve.eps](#)

[eaton-manual-motor-starters-characteristic-pkzm4-characteristic-curve-002.eps](#)

[eaton-manual-motor-starters-characteristic-pkzm4-characteristic-curve.eps](#)

DECLARATIONS OF CONFORMITY

[DA-DC-00004960.pdf](#)

[DA-DC-00004953.pdf](#)

DRAWINGS

[eaton-manual-motor-starters-circuit-breaker-pkzm4-dimensions.eps](#)

[eaton-manual-motor-starters-pkzm4-characteristic-curve-002-de.eps](#)

[eaton-manual-motor-starters-pkzm4-3d-drawing-002.eps](#)

[eaton-manual-motor-starters-mounting-3d-drawing-002.eps](#)

[eaton-general-ie-ready-dilm-contactor-standards.eps](#)

[eaton-manual-motor-starters-pkzm4-3d-drawing.eps](#)

ECAD MODEL	ETN.158253.edz
INSTALLATION INSTRUCTIONS	eaton-motors-starters-pkzm4-motor-protective-circuit-breaker-instruction-leaflet-il03407012z.pdf
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MANUALS AND USER GUIDES	eaton-motor-protective-circuit-breaker-pkzm4-overload-monitoring-exe-manual-mn03402002z-de-de-en-us.pdf
MCAD MODEL	pkzm4_ak.stp pkzm4_ak.dwg
SALES NOTES	eaton-link-module-for-motor-starters-pkz-flyer-fl034003en-en-us.pdf
WIRING DIAGRAMS	eaton-manual-motor-starters-transformer-pkzm0-wiring-diagram.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

