

HC-DD108-I-CT-F - Contact insert



1584130

<https://www.phoenixcontact.com/us/products/1584130>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert, number of positions: 108+PE, size: B24, number of connections per position: 1, Socket, Crimp connection, 250 V, 10 A, 0.14 mm² ... 2.5 mm², application: Signal

Your advantages

- Can be used in rail vehicles, satisfy DIN EN 45545-2 with requirement sets R22, R23, and R24 in hazard levels HL1, HL2, and HL3.

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1584130 |
| Packing unit | 1 pc |
| Sales key | BF61 |
| Product key | BF7ABF |
| Catalog page | Page 539 (C-2-2019) |
| GTIN | 4046356133449 |
| Weight per piece (including packing) | 79.32 g |
| Weight per piece (excluding packing) | 79 g |
| Customs tariff number | 85389099 |
| Country of origin | CN |

HC-DD108-I-CT-F - Contact insert

1584130

<https://www.phoenixcontact.com/us/products/1584130>



Technical data

Notes

| | |
|---------|-----------------------------------------------------------------------------------------------------------------------|
| General | For housing HC-B24 |
| General | Connectors may be operated only when there is no load/voltage. |
| General | It is imperative that guide pins (HC-CST) and sockets (HC-CBU) are used to prevent tip collision due to misalignment. |

Mounting

| | |
|-----------------------|-------------------------------------------------------------------------------------------|
| Assembly instructions | To ensure correct use, installation in housing with IP54 protection or better is required |
|-----------------------|-------------------------------------------------------------------------------------------|


Product properties

| | |
|------------------------------------|----------------------------------------------|
| Type | B24 B48 |
| Product type | Contact insert with a fixed no. of positions |
| Number of positions | 108 |
| Connection profile | 108+PE |
| Contact numbering | 1 - 108 |
| Application | Signal |
| Number of connections per position | 1 |
| Contact material type | turned rolled |
| Series | HC-DD |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Dimensions

| | |
|---------------------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Width | 34 mm |
| Height | 34.5 mm |
| Length | 111 mm |
| Drill hole distance, horizontal | 104 mm |
| Drill hole distance, vertical | 27 mm |

Mechanical characteristics

| | |
|------------------------|--------|
| Minimum housing height | 72 mm |
| Contact diameter | 1.6 mm |

HC-DD108-I-CT-F - Contact insert



1584130

<https://www.phoenixcontact.com/us/products/1584130>

Connection data

Connection technology

| | |
|------------------------------------|------------------|
| Connection technology | Crimp connection |
| Number of connections per position | 1 |
| Connection in acc. with standard | IEC / EN |

Conductor connection

| | |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Conductor cross section | 0.14 mm² ... 2.5 mm² |
| Connection cross section AWG | 26 ... 14 |
| Tightening torque | 0.8 Nm ... 1.2 Nm (PE connection) 0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing) |
| Stripping length of the individual wire | 8 mm (0.14 mm² ... 1.5 mm²) |
| | 6 mm (2.5 mm²) |

Electrical properties

| | |
|-----------------------|----------------|
| Rated voltage (III/3) | 250 V |
| Rated surge voltage | 4 kV |
| Rated current | 10 A |
| SCCR | 5 kA (UL 2237) |

Mechanical properties

Mechanical data

| | |
|-----------------------------|-------|
| Insertion/withdrawal cycles | ≥ 500 |
|-----------------------------|-------|

Material specifications

| | |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Flammability rating according to UL 94 | V0 |
| Contact material | Copper alloy |
| Contact surface material | Ag (alternatively Au) |
| Contact carrier material | PC |
| Standards/regulations | PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3) |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|------------------------------------------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C (including heating up of contacts) |
|---------------------------------|------------------------------------------------------|

Standards and regulations

| | |
|----------------------------------------|----------------------------|
| Constructional and testing regulations | DIN VDE 0627/86 |
| | DIN VDE 0110/02.79 |
| | DIN VDE 0110-1/04.97 |
| | IEC 60664-1, DIN IEC 60512 |
| | IEC 60352 |

HC-DD108-I-CT-F - Contact insert



1584130

<https://www.phoenixcontact.com/us/products/1584130>

| | |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------|
| Tests | DIN VDE 0627/86 |
| | DIN VDE 0110/02.79 |
| | DIN VDE 0110-1/04.97 |
| | IEC 60664-1, DIN IEC 60512 |
| | IEC 60352 |
| Testing | |
| Standards/regulations | PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3) |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com