

HC-D 64-A-UT-PEL-F - Terminal adapter



1584295

<https://www.phoenixcontact.com/no/products/1584295>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON terminal adapter female insert, D64 series, 64-pos., right protective conductor connection for the left side of the control cabinet, screw connection

Commercial data

Item number	1584295
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	31BBF
Product key	BF7ADE
Catalog page	Page 537 (C-2-2019)
GTIN	4046356142366
Weight per piece (including packing)	538 g
Weight per piece (excluding packing)	527.8 g
Customs tariff number	85366990
Country of origin	CN

HC-D 64-A-UT-PEL-F - Terminal adapter



1584295

<https://www.phoenixcontact.com/no/products/1584295>

Technical data

Notes

General	For HEAVYCON-ADVANCE mounting flange and HEAVYCON panel mounting base of B24 type
General	Connectors may be operated only when there is no load/voltage.

Product properties

Type	B24
Product type	Terminal adapter
Product family	HC-D
Number of positions	64
Connection profile	64+PE
Type	for the left side of the control cabinet
Series	HC-D
Screwdriver blade	0.5 x 3.5 mm

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated voltage (III/3)	250 V
Rated surge voltage	4 kV
Rated current	10 A
SCCR	5 kA (UL 2237)

Connection data

Connection technology

Connection technology	Screw connection
Connection in acc. with standard	IEC / EN

Conductor connection

Conductor cross section	0.2 mm ² ... 2.5 mm ²
Connection cross section AWG	22 ... 12
Tightening torque	0.5 Nm ... 0.8 Nm
Stripping length of the individual wire	10 mm


Dimensions

HC-D 64-A-UT-PEL-F - Terminal adapter



1584295

<https://www.phoenixcontact.com/no/products/1584295>

Dimensional drawing	
Width	34 mm
Height	132.6 mm
Length	110 mm
Drill hole distance, horizontal	104 mm
Drill hole distance, vertical	27 mm

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA
Standards/regulations	PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Cable/line

Stripping length of the individual wire	10 mm
---	-------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Standards and regulations

Constructional and testing regulations	DIN EN 61984
	DIN EN 60664
	IEC 60352
Tests	DIN EN 61984
	DIN EN 60664
	IEC 60352

Testing

Standards/regulations	PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
-----------------------	---

Mounting

HC-D 64-A-UT-PEL-F - Terminal adapter



1584295

<https://www.phoenixcontact.com/no/products/1584295>

Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required
	Not for HC-EVO panel mounting bases
	Not for HC-EVO panel mounting bases
	Not for HC-B 24-AMQ-EMV housings


HC-D 64-A-UT-PEL-F - Terminal adapter

1584295

<https://www.phoenixcontact.com/no/products/1584295>


Drawings

Diagram



Derating diagram for 2.5 mm²

Dimensional drawing




Dimensional drawing

HC-D 64-A-UT-PEL-F - Terminal adapter

1584295

<https://www.phoenixcontact.com/no/products/1584295>

Application drawing




Mounting position PE connection left/right (PEL/PER)

HC-D 64-A-UT-PEL-F - Terminal adapter

1584295

<https://www.phoenixcontact.com/no/products/1584295>

Dimensional drawing



Dimensional drawing, side view

HC-D 64-A-UT-PEL-F - Terminal adapter



1584295

<https://www.phoenixcontact.com/no/products/1584295>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/no/products/1584295>

 CSA Approval ID: 13631				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	7 A	- 14	-

 UL Recognized Approval ID: E118976				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	7 A	- 14	-

 EAC Approval ID: RU C-DE.AI30.B.01102				
--	--	--	--	--

 UL Recognized Approval ID: E468743				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	7 A	-	-

HC-D 64-A-UT-PEL-F - Terminal adapter



1584295

<https://www.phoenixcontact.com/no/products/1584295>

Classifications

ECLASS

ECLASS-11.0	27440222
ECLASS-12.0	27440222
ECLASS-13.0	27440222

ETIM

ETIM 9.0	EC000438
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

HC-D 64-A-UT-PEL-F - Terminal adapter



1584295

<https://www.phoenixcontact.com/no/products/1584295>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT AS
Strømsveien 344
N-1081 Oslo
+47 22 07 68 00
norge@phoenixcontact.com