

# HC-B 10-SMLD-52/M2M20 - Housing



1586808

<https://www.phoenixcontact.com/au/products/1586808>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting base, with single locking latch, height 52 mm, with screw connection, 2x M20, with protective cover

## Commercial data

Item number	1586808
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BF7AAC
Product key	BF7AAC
Catalog page	Page 572 (PC-2011)
GTIN	4046356426893
Weight per piece (including packing)	294.95 g
Weight per piece (excluding packing)	294.95 g
Customs tariff number	85389099
Country of origin	DE

# HC-B 10-SMLD-52/M2M20 - Housing

1586808

<https://www.phoenixcontact.com/au/products/1586808>




## Technical data

### Product properties

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Type	B10
No. of cable outlets	2
Type of the screw connection	2x M20
Protective cover	yes
Shielded	no
Cable outlet	lateral
Pg screw connection	with

### Dimensions

Dimensional drawing	
Width	52 mm
Height	52 mm
Length	93 mm
Wrench size, union nut	20 mm

### Material specifications

Material Screw connection	Brass, nickel-plated
Material Protective cover	PA
Seal material Cable seal	NBR
Housing material	die-cast aluminum
Housing surface material	Powder-coated, gray
Locking latch material	Stainless steel, handle: PA

### Mechanical properties

#### Mechanical data

Type of the screw connection	2x M20
Locking type	Latch

### Cable/line

External cable diameter Cable 1	5 mm ... 12 mm (Cable 1)
External cable diameter Cable 2	5 mm ... 12 mm (Cable 2)

### Connection data

# HC-B 10-SMLD-52/M2M20 - Housing

1586808

<https://www.phoenixcontact.com/au/products/1586808>



External cable diameter	5 mm ... 12 mm (Cable 1)
-------------------------	--------------------------

## Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP65 (When plugged in)
	IP54 (with closed protective cover)
Ambient temperature (operation)	-40 °C ... 125 °C

# HC-B 10-SMLD-52/M2M20 - Housing


1586808

<https://www.phoenixcontact.com/au/products/1586808>



## Drawings

Dimensional drawing



Dimensional drawing

# HC-B 10-SMLD-52/M2M20 - Housing



1586808

<https://www.phoenixcontact.com/au/products/1586808>

## Classifications

### ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202

### UNSPSC

UNSPSC 21.0	31261501
-------------	----------

# HC-B 10-SMLD-52/M2M20 - Housing

1586808

<https://www.phoenixcontact.com/au/products/1586808>



## Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

# HC-B 10-SMLD-52/M2M20 - Housing

1586808

<https://www.phoenixcontact.com/au/products/1586808>



## Accessories

### HC-M-KV-M20(9-13) - Cable gland

1690561

<https://www.phoenixcontact.com/au/products/1690561>



Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 9 - 13 mm, WAF 22, screw connection: M20

---

### HC-M-KV-M20(11-16) - Cable gland

1645998

<https://www.phoenixcontact.com/au/products/1645998>



Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 11 - 16 mm, WAF 27, screw connection: M20

# HC-B 10-SMLD-52/M2M20 - Housing

1586808

<https://www.phoenixcontact.com/au/products/1586808>



## HC-M-KV-M20(1ASI) - Cable gland

1584017

<https://www.phoenixcontact.com/au/products/1584017>



Metal screw connection for an AS-Interface flat-ribbon conductor, thread type M20

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd

Unit 7, 2-8 South Street

Rydalmere NSW 2116

1300 786 411

[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)